

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P761073

Luminaire Tested: LD6D15D010-EU6DR2015309040-6LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P761073
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D15D010-EU6DR2015309040-6LBS1H
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1690.0 lumens
Efficiency: N/A
Efficacy: 107.0 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P761073

CATALOG NUMBER: LD6D15D010-EU6DR2015309040-6LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P761073

CATALOG NUMBER: LD6D15D010-EU6DR2015309040-6LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	113	111	109	108	107	106	104		103	102	101		100
2	111	108	105	102	109	106	104	101	103	101	99		100	99	97		98
3	108	103	100	97	106	102	99	96	100	97	95		97	95	93		95
4	105	99	96	93	103	98	95	92	96	93	91		95	92	90		93
5	102	96	92	89	100	95	91	89	94	90	88		92	89	87		91
6	99	93	89	86	98	92	88	86	91	87	85		90	87	84		88
7	96	90	86	83	95	89	86	83	88	85	82		87	84	82		86
8	94	87	83	81	93	87	83	80	86	83	80		85	82	80		84
9	91	85	81	78	91	85	81	78	84	80	78		83	80	78		82
10	89	83	79	76	88	82	79	76	82	78	76		81	78	76		81

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1050990
5°	948189
10°	532176
15°	270515
20°	114529
25°	52876
30°	27983
35°	15086
40°	8059
45°	4759
50°	2771
55°	1467
60°	940
65°	672
70°	288
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4759 cd/sqm

TEST NUMBER: P761073

CATALOG NUMBER: LD6D15D010-EU6DR2015309040-6LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	684.9	40.5
10°-20°	674.4	39.9
20°-30°	220.3	13.0
30°-40°	75.0	4.4
40°-50°	25.2	1.5
50°-60°	7.6	0.4
60°-70°	2.5	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1579.6	93.5
0°-40°	1654.6	97.9
0°-60°	1687.4	99.8
0°-90°	1690.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1690.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9619	
5°	8645	685
15°	2392	674
25°	439	220
35°	113	75
45°	31	25
55°	8	8
65°	3	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P761073

CATALOG NUMBER: LD6D15D010-EU6DR2015309040-6LBS1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	9619.1
0.5°	9619.1
1°	9607.1
1.5°	9583.2
2°	9539.5
2.5°	9481.2
3°	9399.0
3.5°	9284.2
4°	9113.8
4.5°	8906.5
5°	8645.2
5.5°	8301.8
6°	7949.7
6.5°	7546.3
7°	7151.4
7.5°	6688.9
8°	6276.0
8.5°	5860.6
9°	5476.8
9.5°	5124.8
10°	4796.7
12.5°	3444.2
15°	2391.5
17.5°	1562.4
20°	985.0
22.5°	638.1
25°	438.6
27.5°	308.4
30°	221.8
32.5°	159.3
35°	113.1
37.5°	78.8
40°	56.5
42.5°	41.1
45°	30.8
47.5°	24.0
50°	16.3
52.5°	10.3
55°	7.7
57.5°	6.0
60°	4.3
62.5°	3.4
65°	2.6



TEST NUMBER: P761073

CATALOG NUMBER: LD6D15D010-EU6DR2015309040-6LBS1H

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	1.7
70°	0.9



(END OF REPORT)