

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P762007

Luminaire Tested: LD6D20D010-EU6DR2015309024-6LBDP1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P762007
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D20D010-EU6DR2015309024-6LBDP1MW
Description: 6 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1634.0 lumens
Efficiency: N/A
Efficacy: 70.7 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P762007

CATALOG NUMBER: LD6D20D010-EU6DR2015309024-6LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P762007

CATALOG NUMBER: LD6D20D010-EU6DR2015309024-6LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	115	113	111	109	113	111	109	108	107	106	104		103	102	101		97
2	111	108	105	102	109	106	104	101	103	101	99		100	99	97		94
3	108	103	100	97	106	102	99	96	100	97	95		97	95	93		91
4	105	99	96	93	103	98	95	92	96	93	91		95	92	90		88
5	102	96	92	89	100	95	91	89	94	90	88		92	89	87		85
6	99	93	89	86	98	92	88	86	91	87	85		90	87	84		83
7	96	90	86	83	95	89	86	83	88	85	82		87	84	82		81
8	94	87	83	81	93	87	83	80	86	83	80		85	82	80		79
9	91	85	81	78	91	85	81	78	84	80	78		83	80	78		77
10	89	83	79	76	88	82	79	76	82	78	76		81	78	76		75

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1016136
5°	916745
10°	514524
15°	261545
20°	110738
25°	51116
30°	27062
35°	14579
40°	7802
45°	4605
50°	2669
55°	1429
60°	896
65°	646
70°	256
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 4605 cd/sqm



TEST NUMBER: P762007

CATALOG NUMBER: LD6D20D010-EU6DR2015309024-6LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	662.2	40.5
10°-20°	652.0	39.9
20°-30°	213.0	13.0
30°-40°	72.5	4.4
40°-50°	24.4	1.5
50°-60°	7.3	0.4
60°-70°	2.4	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1527.2	93.5
0°-40°	1599.7	97.9
0°-60°	1631.4	99.8
0°-90°	1634.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1634.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9300	
5°	8358	662
15°	2312	652
25°	424	213
35°	109	73
45°	30	24
55°	8	7
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P762007

CATALOG NUMBER: LD6D20D010-EU6DR2015309024-6LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	9300.1
0.5°	9300.1
1°	9288.5
1.5°	9265.3
2°	9223.1
2.5°	9166.7
3°	9087.2
3.5°	8976.3
4°	8811.5
4.5°	8611.1
5°	8358.5
5.5°	8026.4
6°	7686.0
6.5°	7296.0
7°	6914.2
7.5°	6467.0
8°	6067.8
8.5°	5666.2
9°	5295.2
9.5°	4954.8
10°	4637.6
12.5°	3330.0
15°	2312.2
17.5°	1510.5
20°	952.4
22.5°	617.0
25°	424.0
27.5°	298.1
30°	214.5
32.5°	154.0
35°	109.3
37.5°	76.2
40°	54.7
42.5°	39.8
45°	29.8
47.5°	23.2
50°	15.7
52.5°	9.9
55°	7.5
57.5°	5.8
60°	4.1
62.5°	3.3
65°	2.5



TEST NUMBER: P762007

CATALOG NUMBER: LD6D20D010-EU6DR2015309024-6LBDP1MW

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	1.7
70°	0.8



(END OF REPORT)