

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P762034

Luminaire Tested: LD6D20D010-EU6DR2015309030-6LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P762034
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D20D010-EU6DR2015309030-6LBS1B
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2001.7 lumens
Efficiency: N/A
Efficacy: 86.7 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 23.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P762034

CATALOG NUMBER: LD6D20D010-EU6DR2015309030-6LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P762034

CATALOG NUMBER: LD6D20D010-EU6DR2015309030-6LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	113	111	109	108	107	106	104		103	102	101		100
2	111	108	105	102	109	106	104	101	103	101	99		100	99	97		98
3	108	103	100	97	106	102	99	96	100	97	95		97	95	93		95
4	105	99	96	93	103	98	95	92	96	93	91		95	92	90		93
5	102	96	92	89	100	95	91	89	94	90	88		92	89	87		91
6	99	93	89	86	98	92	88	86	91	87	85		90	87	84		88
7	96	90	86	83	95	89	86	83	88	85	82		87	84	82		86
8	94	87	83	81	93	87	83	80	86	83	80		85	82	80		84
9	91	85	81	78	91	85	81	78	84	80	78		83	80	78		82
10	89	83	79	76	88	82	79	76	82	78	76		81	78	76		81

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1244841
5°	1123082
10°	630330
15°	320410
20°	135656
25°	62617
30°	33156
35°	17860
40°	9556
45°	5640
50°	3281
55°	1733
60°	1114
65°	776
70°	319
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5640 cd/sqm



TEST NUMBER: P762034

CATALOG NUMBER: LD6D20D010-EU6DR2015309030-6LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	811.2	40.5
10°-20°	798.8	39.9
20°-30°	260.9	13.0
30°-40°	88.8	4.4
40°-50°	29.9	1.5
50°-60°	9.0	0.4
60°-70°	3.0	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1870.9	93.5
0°-40°	1959.7	97.9
0°-60°	1998.6	99.8
0°-90°	2001.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2001.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	11393	
5°	10240	811
15°	2833	799
25°	519	261
35°	134	89
45°	36	30
55°	9	9
65°	3	3
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P762034

CATALOG NUMBER: LD6D20D010-EU6DR2015309030-6LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	11393.3
0.5°	11393.3
1°	11379.1
1.5°	11350.7
2°	11299.0
2.5°	11230.0
3°	11132.6
3.5°	10996.6
4°	10794.7
4.5°	10549.2
5°	10239.8
5.5°	9832.9
6°	9416.0
6.5°	8938.1
7°	8470.4
7.5°	7922.6
8°	7433.6
8.5°	6941.5
9°	6487.0
9.5°	6070.0
10°	5681.4
12.5°	4079.5
15°	2832.6
17.5°	1850.5
20°	1166.7
22.5°	755.8
25°	519.4
27.5°	365.2
30°	262.8
32.5°	188.7
35°	133.9
37.5°	93.3
40°	67.0
42.5°	48.7
45°	36.5
47.5°	28.4
50°	19.3
52.5°	12.2
55°	9.1
57.5°	7.1
60°	5.1
62.5°	4.1
65°	3.0



TEST NUMBER: P762034

CATALOG NUMBER: LD6D20D010-EU6DR2015309030-6LBS1B

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	2.0
70°	1.0



(END OF REPORT)