

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P763805

Luminaire Tested: LD6D30D010-EU6DR1515309024-6LBS1MW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P763805
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-21)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D30D010-EU6DR1515309024-6LBS1MW
Description: 6 INCH ROUND SHALLOW MATTE WHITE TRIM, WITH 15° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2808.1 lumens
Efficiency: N/A
Efficacy: 96.8 lumens/watt
Spacing Criteria (0/90/45): 0.22 / 0.22 / 0.23
Luminous Opening: Vertical Cylinder (Dia: 0.35' x H: 0.35')
CIE Type: Direct

Input Watts (W): 29
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P763805

CATALOG NUMBER: LD6D30D010-EU6DR1515309024-6LBS1MW

Luminous Intensity Polar Plot



TEST NUMBER: P763805

CATALOG NUMBER: LD6D30D010-EU6DR1515309024-6LBS1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10			50	30	10			0
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111			106	106	106			100
1	116	114	112	111	113	112	110	109		108	107	106			104	103	103			98
2	113	110	107	105	111	108	106	104		105	103	102			102	101	100			96
3	110	106	103	101	108	105	102	100		103	100	99			100	99	97			94
4	108	103	100	98	106	102	99	97		100	98	96			99	97	95			93
5	106	101	98	95	104	100	97	95		98	96	94			97	95	93			92
6	104	99	95	93	102	98	95	93		97	94	92			96	93	92			90
7	102	97	94	91	101	96	93	91		95	93	91			94	92	90			89
8	100	95	92	90	99	95	92	90		94	91	89			93	91	89			88
9	99	93	90	88	98	93	90	88		92	90	88			92	89	88			87
10	97	92	89	87	96	92	89	87		91	89	87			91	88	87			86

AVERAGE LUMINANCE (cd/sqm):

	0°	45°	90°
0°	4305024	4305024	4305024
5°	2529838	2497073	2516830
10°	755036	760326	771962
15°	187811	191467	185561
20°	56188	65074	57382
25°	19810	25232	20059
30°	7278	9585	7398
35°	3645	4118	3529
40°	2301	2528	2301
45°	1701	1813	1701
50°	1349	1349	1349
55°	1128	1128	1128
60°	913	913	913
65°	692	692	692
70°	592	592	592
75°	370	370	491
80°	252	252	252
85°	133	133	133

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 45°

Vertical Angle: 45°

Luminance: 1813 cd/sqm

TEST NUMBER: P763805

CATALOG NUMBER: LD6D30D010-EU6DR1515309024-6LBS1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1821.3	64.9
10°-20°	749.1	26.7
20°-30°	148.8	5.3
30°-40°	37.1	1.3
40°-50°	19.5	0.7
50°-60°	14.5	0.5
60°-70°	10.2	0.4
70°-80°	5.8	0.2
80°-90°	1.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2719.2	96.8
0°-40°	2756.3	98.2
0°-60°	2790.3	99.4
0°-90°	2808.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2808.1	100.0

CANDELA DISTRIBUTION:

	0°	22.5°	45°	67.5°	90°	Flux
0°	38260	38260	38260	38260	38260	
5°	24893	24637	24570	24741	24765	1818
15°	2162	2203	2204	2166	2136	741
25°	254	288	324	287	258	134
35°	50	53	57	53	49	34
45°	24	24	26	24	24	19
55°	16	16	16	16	16	14
65°	10	10	10	10	10	10
75°	5	5	5	5	6	6
85°	2	2	2	2	2	2
90°	0	0	0	0	0	

TEST NUMBER: P763805

CATALOG NUMBER: LD6D30D010-EU6DR1515309024-6LBS1MW

CANDELA DISTRIBUTION (FULL):

	0°	22.5°	45°	67.5°	90°
0°	38260.1	38260.1	38260.1	38260.1	38260.1
2.5°	34512.1	34541.3	34552.6	34586.6	34713.0
5°	24892.9	24636.9	24570.5	24740.6	24764.9
7.5°	14745.6	14797.4	14986.9	15029.0	14876.8
10°	8091.9	8158.3	8148.6	8206.9	8273.3
12.5°	4138.3	4086.5	4070.3	4136.7	4044.3
15°	2162.3	2202.8	2204.4	2165.5	2136.4
17.5°	1162.9	1209.9	1287.6	1224.5	1127.3
20°	686.7	728.9	795.3	743.4	701.3
22.5°	424.4	458.4	505.3	464.8	430.8
25°	254.3	288.3	323.9	286.7	257.5
27.5°	150.6	179.8	202.5	178.2	149.0
30°	97.2	113.4	128.0	111.8	98.8
32.5°	68.0	74.5	81.0	74.5	68.0
35°	50.2	53.4	56.7	53.4	48.6
37.5°	38.9	42.1	43.7	40.5	37.3
40°	32.4	34.0	35.6	34.0	32.4
42.5°	27.5	29.2	29.2	29.2	27.5
45°	24.3	24.3	25.9	24.3	24.3
47.5°	21.1	21.1	22.7	21.1	21.1
50°	19.4	19.4	19.4	19.4	19.4
52.5°	17.8	17.8	17.8	17.8	17.8
55°	16.2	16.2	16.2	16.2	16.2
57.5°	14.6	14.6	14.6	14.6	14.6
60°	13.0	13.0	13.0	13.0	13.0
62.5°	11.3	11.3	11.3	11.3	11.3
65°	9.7	9.7	9.7	9.7	9.7
67.5°	9.7	9.7	9.7	9.7	9.7
70°	8.1	8.1	8.1	8.1	8.1
72.5°	6.5	6.5	6.5	6.5	6.5
75°	4.9	4.9	4.9	4.9	6.5
77.5°	4.9	4.9	4.9	4.9	4.9
80°	3.2	3.2	3.2	3.2	3.2
82.5°	3.2	3.2	3.2	3.2	3.2
85°	1.6	1.6	1.6	1.6	1.6
87.5°	0.0	0.0	0.0	0.0	0.0
90°	0.0	0.0	0.0	0.0	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180° - - 45°-225° - - - 90°-270°







(END OF REPORT)