

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P763908

Luminaire Tested: LD6D30D010-EU6DR2015309030-6LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P763908
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D30D010-EU6DR2015309030-6LBS1LI
Description: 6 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3732.7 lumens
Efficiency: N/A
Efficacy: 128.7 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 29
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P763908

CATALOG NUMBER: LD6D30D010-EU6DR2015309030-6LBS1LI

Luminous Intensity Polar Plot



TEST NUMBER: P763908

CATALOG NUMBER: LD6D30D010-EU6DR2015309030-6LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	113	111	109		113	111	109	108		107	106	104		103	102	101		100	99	98
2	111	108	105	102		109	106	104	101		103	101	99		100	99	97		98	96	95
3	108	103	100	97		106	102	99	96		100	97	95		97	95	93		95	93	92
4	105	99	96	93		103	98	95	92		96	93	91		95	92	90		93	91	89
5	102	96	92	89		100	95	91	89		94	90	88		92	89	87		91	88	86
6	99	93	89	86		98	92	88	86		91	87	85		90	87	84		88	86	84
7	96	90	86	83		95	89	86	83		88	85	82		87	84	82		86	84	82
8	94	87	83	81		93	87	83	80		86	83	80		85	82	80		84	82	80
9	91	85	81	78		91	85	81	78		84	80	78		83	80	78		82	80	78
10	89	83	79	76		88	82	79	76		82	78	76		81	78	76		81	78	76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2321321
5°	2094260
10°	1175420
15°	597485
20°	252975
25°	116770
30°	61820
35°	33306
40°	17814
45°	10523
50°	6102
55°	3238
60°	2076
65°	1474
70°	607
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10523 cd/sqm



TEST NUMBER: P763908

CATALOG NUMBER: LD6D30D010-EU6DR2015309030-6LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1512.7	40.5
10°-20°	1489.5	39.9
20°-30°	486.6	13.0
30°-40°	165.7	4.4
40°-50°	55.7	1.5
50°-60°	16.8	0.4
60°-70°	5.6	0.2
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3488.7	93.5
0°-40°	3654.4	97.9
0°-60°	3726.9	99.8
0°-90°	3732.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3732.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	21246	
5°	19095	###
15°	5282	1489
25°	969	487
35°	250	166
45°	68	56
55°	17	17
65°	6	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P763908

CATALOG NUMBER: LD6D30D010-EU6DR2015309030-6LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	21245.7
0.5°	21245.7
1°	21219.2
1.5°	21166.2
2°	21069.8
2.5°	20941.1
3°	20759.5
3.5°	20506.0
4°	20129.5
4.5°	19671.7
5°	19094.6
5.5°	18336.0
6°	17558.4
6.5°	16667.4
7°	15795.2
7.5°	14773.6
8°	13861.7
8.5°	12944.2
9°	12096.6
9.5°	11319.1
10°	10594.5
12.5°	7607.2
15°	5282.1
17.5°	3450.8
20°	2175.7
22.5°	1409.4
25°	968.6
27.5°	681.1
30°	490.0
32.5°	351.9
35°	249.7
37.5°	174.1
40°	124.9
42.5°	90.8
45°	68.1
47.5°	53.0
50°	35.9
52.5°	22.7
55°	17.0
57.5°	13.2
60°	9.5
62.5°	7.6
65°	5.7



TEST NUMBER: P763908

CATALOG NUMBER: LD6D30D010-EU6DR2015309030-6LBS1LI

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	3.8
70°	1.9



(END OF REPORT)