

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P763916

Luminaire Tested: LD6D30D010-EU6DR2015309035-6LBDP1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P763916
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D30D010-EU6DR2015309035-6LBDP1H
Description: 6 INCH ROUND DEEP 45° CUTOFF SEMI-SPECULAR CLEAR TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3565.2 lumens
Efficiency: N/A
Efficacy: 122.9 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 29
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P763916

CATALOG NUMBER: LD6D30D010-EU6DR2015309035-6LBDP1H

Luminous Intensity Polar Plot





TEST NUMBER: P763916

CATALOG NUMBER: LD6D30D010-EU6DR2015309035-6LBDP1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	115	113	111	109		113	111	109	108		107	106	104		103	102	101		100	99	98
2	111	108	105	102		109	106	104	101		103	101	99		100	99	97		98	96	95
3	108	103	100	97		106	102	99	96		100	97	95		97	95	93		95	93	92
4	105	99	96	93		103	98	95	92		96	93	91		95	92	90		93	91	89
5	102	96	92	89		100	95	91	89		94	90	88		92	89	87		91	88	86
6	99	93	89	86		98	92	88	86		91	87	85		90	87	84		88	86	84
7	96	90	86	83		95	89	86	83		88	85	82		87	84	82		86	84	82
8	94	87	83	81		93	87	83	80		86	83	80		85	82	80		84	82	80
9	91	85	81	78		91	85	81	78		84	80	78		83	80	78		82	80	78
10	89	83	79	76		88	82	79	76		82	78	76		81	78	76		81	78	76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2217174
5°	2000309
10°	1122688
15°	570677
20°	241615
25°	111538
30°	59044
35°	31812
40°	17016
45°	10059
50°	5830
55°	3105
60°	1967
65°	1396
70°	575
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 10059 cd/sqm



TEST NUMBER: P763916

CATALOG NUMBER: LD6D30D010-EU6DR2015309035-6LBDP1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1444.8	40.5
10°-20°	1422.7	39.9
20°-30°	464.8	13.0
30°-40°	158.2	4.4
40°-50°	53.2	1.5
50°-60°	16.0	0.4
60°-70°	5.3	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3332.2	93.5
0°-40°	3490.4	97.9
0°-60°	3559.7	99.8
0°-90°	3565.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3565.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	20292	
5°	18238	###
15°	5045	1423
25°	925	465
35°	238	158
45°	65	53
55°	16	16
65°	5	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P763916

CATALOG NUMBER: LD6D30D010-EU6DR2015309035-6LBDP1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	20292.5
0.5°	20292.5
1°	20267.2
1.5°	20216.6
2°	20124.5
2.5°	20001.6
3°	19828.1
3.5°	19586.0
4°	19226.4
4.5°	18789.1
5°	18238.0
5.5°	17513.4
6°	16770.7
6.5°	15919.6
7°	15086.6
7.5°	14110.8
8°	13239.8
8.5°	12363.4
9°	11553.9
9.5°	10811.2
10°	10119.2
12.5°	7265.9
15°	5045.1
17.5°	3296.0
20°	2078.0
22.5°	1346.2
25°	925.2
27.5°	650.5
30°	468.0
32.5°	336.1
35°	238.5
37.5°	166.2
40°	119.3
42.5°	86.7
45°	65.1
47.5°	50.6
50°	34.3
52.5°	21.7
55°	16.3
57.5°	12.6
60°	9.0
62.5°	7.2
65°	5.4



TEST NUMBER: P763916

CATALOG NUMBER: LD6D30D010-EU6DR2015309035-6LBDP1H

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	3.6
70°	1.8



(END OF REPORT)