

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P771589

Luminaire Tested: LD6D75BD010-EU6DR6070959050-6LBS1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P771589
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-60)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D75BD010-EU6DR6070959050-6LBS1B
Description: 6 INCH ROUND SHALLOW SPECULAR BLACK TRIM, WITH 60° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8990.2 lumens
Efficiency: N/A
Efficacy: 124.2 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 72.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P771589

CATALOG NUMBER: LD6D75BD010-EU6DR6070959050-6LBS1B

Luminous Intensity Polar Plot





TEST NUMBER: P771589

CATALOG NUMBER: LD6D75BD010-EU6DR6070959050-6LBS1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	108	106	111	109	106	104	105	103	101	101	99	98	97	96	95	94		
2	108	103	99	96	106	101	98	95	98	95	92	95	93	90	92	90	89	87		
3	102	96	91	87	100	95	90	86	92	88	85	90	86	84	87	85	82	81		
4	97	90	84	80	95	88	83	79	86	82	78	84	81	78	82	79	77	75		
5	92	84	78	74	91	83	77	73	81	76	73	79	75	72	78	74	71	70		
6	87	79	73	68	86	78	72	68	76	71	68	75	70	67	74	70	67	65		
7	83	74	68	63	82	73	67	63	72	67	63	71	66	63	69	65	62	61		
8	79	69	63	59	78	69	63	59	68	63	59	67	62	59	66	61	58	57		
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	55	53		
10	72	62	56	52	71	61	56	52	61	55	52	60	55	52	59	55	52	50		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	982997
5°	980599
10°	1013173
15°	1014212
20°	933183
25°	793740
30°	604802
35°	427692
40°	251143
45°	101333
50°	33843
55°	16287
60°	6687
65°	982
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 101333 cd/sqm



TEST NUMBER: P771589

CATALOG NUMBER: LD6D75BD010-EU6DR6070959050-6LBS1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	862.5	9.6
10°-20°	2483.9	27.6
20°-30°	2973.0	33.1
30°-40°	1988.5	22.1
40°-50°	589.5	6.6
50°-60°	84.8	0.9
60°-70°	8.1	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	6319.4	70.3
0°-40°	8307.8	92.4
0°-60°	8982.2	99.9
0°-90°	8990.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8990.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8997	
5°	8941	862
15°	8966	2484
25°	6584	2973
35°	3206	1988
45°	656	590
55°	86	85
65°	4	8
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P771589

CATALOG NUMBER: LD6D75BD010-EU6DR6070959050-6LBS1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	8996.8
2.5°	8985.3
5°	8940.7
7.5°	9061.9
10°	9132.1
12.5°	9119.3
15°	8966.2
17.5°	8605.1
20°	8025.8
22.5°	7330.4
25°	6584.0
27.5°	5743.1
30°	4793.8
32.5°	3946.6
35°	3206.5
37.5°	2465.2
40°	1760.8
42.5°	1161.1
45°	655.8
47.5°	335.6
50°	199.1
52.5°	128.9
55°	85.5
57.5°	54.9
60°	30.6
62.5°	12.8
65°	3.8
67.5°	1.3
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)