

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P773034

Luminaire Tested: LD6D85BD010-EU6DR5570959030-6LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P773034
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D85BD010-EU6DR5570959030-6LBS1LI
Description: 6 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 55° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11629.1 lumens
Efficiency: N/A
Efficacy: 132.6 lumens/watt
Spacing Criteria (0/90/45): 0.89 / 0.89 / 0.87
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 87.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P773034

CATALOG NUMBER: LD6D85BD010-EU6DR5570959030-6LBS1LI

Luminous Intensity Polar Plot





TEST NUMBER: P773034

CATALOG NUMBER: LD6D85BD010-EU6DR5570959030-6LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					0
RW	70	50	30	10	70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																				
0	119	119	119	119	116	116	116	116		111	111	111		106	106	106		102	102	102
1	114	111	108	106	111	109	106	104		105	103	101		101	99	98		97	96	95
2	108	103	99	96	106	101	98	95		98	95	92		95	93	90		92	90	89
3	102	96	91	87	100	95	90	86		92	88	85		90	86	84		87	85	82
4	97	90	84	80	95	88	83	79		86	82	78		84	81	78		82	79	77
5	92	84	78	74	91	83	77	73		81	76	73		79	75	72		78	74	71
6	88	79	73	68	86	78	72	68		76	71	68		75	70	67		74	70	67
7	83	74	68	64	82	73	67	63		72	67	63		71	66	63		70	65	62
8	79	69	63	59	78	69	63	59		68	63	59		67	62	59		66	62	58
9	75	66	60	56	74	65	59	55		64	59	55		63	58	55		62	58	55
10	72	62	56	52	71	61	56	52		61	56	52		60	55	52		59	55	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1424793
5°	1368202
10°	1363042
15°	1323887
20°	1187053
25°	981036
30°	741059
35°	537319
40°	343866
45°	157052
50°	51368
55°	22154
60°	9528
65°	1241
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 157052 cd/sqm



TEST NUMBER: P773034

CATALOG NUMBER: LD6D85BD010-EU6DR5570959030-6LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1187.0	10.2
10°-20°	3239.6	27.9
20°-30°	3691.9	31.7
30°-40°	2513.3	21.6
40°-50°	866.1	7.4
50°-60°	119.7	1.0
60°-70°	11.6	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8118.5	69.8
0°-40°	10631.8	91.4
0°-60°	11617.6	99.9
0°-90°	11629.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	11629.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	13040	
5°	12475	###
15°	11704	3240
25°	8138	3692
35°	4028	2513
45°	1016	866
55°	116	120
65°	5	12
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P773034

CATALOG NUMBER: LD6D85BD010-EU6DR5570959030-6LBS1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	13040.3
2.5°	12741.3
5°	12474.7
7.5°	12343.8
10°	12285.6
12.5°	12091.7
15°	11703.9
17.5°	11088.3
20°	10209.2
22.5°	9194.4
25°	8137.6
27.5°	7037.2
30°	5873.8
32.5°	4888.1
35°	4028.4
37.5°	3210.8
40°	2410.9
42.5°	1670.8
45°	1016.4
47.5°	547.8
50°	302.2
52.5°	179.4
55°	116.3
57.5°	74.3
60°	43.6
62.5°	19.4
65°	4.8
67.5°	1.6
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)