

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774099

Luminaire Tested: LD6D95BD010-EU6DR2570959024-6LBS1H

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P774099
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR2570959024-6LBS1H
Description: 6 INCH ROUND SHALLOW SEMI-SPECULAR CLEAR TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 9010.8 lumens
Efficiency: N/A
Efficacy: 90.8 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P774099

CATALOG NUMBER: LD6D95BD010-EU6DR2570959024-6LBS1H

Luminous Intensity Polar Plot





TEST NUMBER: P774099

CATALOG NUMBER: LD6D95BD010-EU6DR2570959024-6LBS1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94
4	103	97	93	90	102	96	93	90	94	91	89		93	90	88		91
5	100	93	89	86	98	93	89	86	91	87	85		89	86	84		88
6	97	90	85	82	95	89	85	82	88	84	81		87	83	81		85
7	93	87	82	79	92	86	82	79	85	81	78		84	80	78		83
8	91	84	79	76	90	83	79	76	82	78	76		81	78	75		80
9	88	81	76	73	87	80	76	73	80	76	73		79	75	73		78
10	85	78	74	71	85	78	74	71	77	73	71		76	73	71		76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3734074
5°	3477816
10°	2480825
15°	1461107
20°	909126
25°	498933
30°	228179
35°	86419
40°	39138
45°	23533
50°	9774
55°	6286
60°	4392
65°	2973
70°	447
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23533 cd/sqm

TEST NUMBER: P774099

CATALOG NUMBER: LD6D95BD010-EU6DR2570959024-6LBS1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2725.2	30.2
10°-20°	3691.0	41.0
20°-30°	1953.2	21.7
30°-40°	482.2	5.4
40°-50°	117.6	1.3
50°-60°	31.0	0.3
60°-70°	10.4	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8369.4	92.9
0°-40°	8851.6	98.2
0°-60°	9000.2	99.9
0°-90°	9010.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	9010.8	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	34176	
5°	31709	###
15°	12917	3691
25°	4139	1953
35°	648	482
45°	152	118
55°	33	31
65°	12	10
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P774099

CATALOG NUMBER: LD6D95BD010-EU6DR2570959024-6LBS1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	34175.8
2.5°	33614.1
5°	31709.3
7.5°	27882.5
10°	22360.6
12.5°	16903.3
15°	12917.0
17.5°	10067.0
20°	7818.9
22.5°	5863.8
25°	4138.6
27.5°	2775.3
30°	1808.6
32.5°	1100.4
35°	647.9
37.5°	396.5
40°	274.4
42.5°	209.7
45°	152.3
47.5°	91.9
50°	57.5
52.5°	41.7
55°	33.0
57.5°	25.9
60°	20.1
62.5°	15.8
65°	11.5
67.5°	4.3
70°	1.4
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)