

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774334

Luminaire Tested: LD6D95BD010-EU6DR4070959024-6LBS1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P774334
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-28)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR4070959024-6LBS1LI
Description: 6 INCH ROUND SHALLOW SPECULAR CLEAR TRIM, WITH 40° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 2400K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 11054.1 lumens
Efficiency: N/A
Efficacy: 111.4 lumens/watt
Spacing Criteria (0/90/45): 0.68 / 0.68 / 0.6
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P774334

CATALOG NUMBER: LD6D95BD010-EU6DR4070959024-6LBS1LI

Luminous Intensity Polar Plot



TEST NUMBER: P774334

CATALOG NUMBER: LD6D95BD010-EU6DR4070959024-6LBS1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	112	110	108	112	110	108	107	106	105	103		103	101	100		99
2	110	106	103	100	108	105	102	99	102	99	97		99	97	95		96
3	106	101	97	94	104	100	96	93	97	94	92		95	93	90		93
4	102	97	92	89	101	95	91	88	93	90	87		92	89	86		90
5	99	92	88	84	97	91	87	84	90	86	83		88	85	83		87
6	95	88	84	80	94	88	83	80	86	82	80		85	82	79		84
7	92	85	80	77	91	84	80	77	83	79	76		82	79	76		81
8	89	82	77	74	88	81	77	74	80	76	73		79	76	73		78
9	86	79	74	71	85	78	74	71	77	73	71		76	73	70		76
10	83	76	71	68	82	75	71	68	75	71	68		74	70	68		73

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2812033
5°	2798371
10°	2645070
15°	2248648
20°	1532616
25°	639465
30°	201067
35°	93448
40°	51675
45°	23703
50°	11508
55°	6305
60°	3278
65°	1163
70°	479
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 23703 cd/sqm



TEST NUMBER: P774334

CATALOG NUMBER: LD6D95BD010-EU6DR4070959024-6LBS1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	2382.4	21.6
10°-20°	5337.2	48.3
20°-30°	2671.6	24.2
30°-40°	489.7	4.4
40°-50°	135.1	1.2
50°-60°	31.7	0.3
60°-70°	6.1	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	10391.2	94.0
0°-40°	10881.0	98.4
0°-60°	11047.8	99.9
0°-90°	11054.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	11054.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	25737	
5°	25514	###
15°	19879	5337
25°	5304	2672
35°	701	490
45°	153	135
55°	33	32
65°	4	6
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P774334

CATALOG NUMBER: LD6D95BD010-EU6DR4070959024-6LBS1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	25736.9
2.5°	25699.3
5°	25514.4
7.5°	24925.0
10°	23841.0
12.5°	22151.1
15°	19879.3
17.5°	16924.9
20°	13181.2
22.5°	8986.4
25°	5304.3
27.5°	2804.0
30°	1593.7
32.5°	1029.9
35°	700.6
37.5°	500.7
40°	362.3
42.5°	248.1
45°	153.4
47.5°	97.7
50°	67.7
52.5°	48.1
55°	33.1
57.5°	21.0
60°	15.0
62.5°	9.0
65°	4.5
67.5°	3.0
70°	1.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9

Signify Classified - Internal
Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269

Scaled Data Report





— 0°-180°







(END OF REPORT)