

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774760

Luminaire Tested: LD6D95BD010-EU6DR6570959035-6LBDP1MW

Issue Date: 2/5/2024

Test Information

Test Method: LM-79-2019
Report Number: P774760
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-59)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/5/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR6570959035-6LBDP1MW
Description: 6 INCH ROUND DEEP 45° CUTOFF MATTE WHITE TRIM, WITH 65° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8541.7 lumens
Efficiency: N/A
Efficacy: 86.1 lumens/watt
Spacing Criteria (0/90/45): 0.98 / 0.98 / 0.92
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P774760

CATALOG NUMBER: LD6D95BD010-EU6DR6570959035-6LBDP1MW

Luminous Intensity Polar Plot





TEST NUMBER: P774760

CATALOG NUMBER: LD6D95BD010-EU6DR6570959035-6LBDP1MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	113	111	108	106		111	108	106	104		104	103	101		101	99	98		97	96	95
2	108	103	99	95		106	101	97	94		98	95	92		95	92	90		92	90	88
3	102	96	91	87		100	94	90	86		92	88	85		89	86	83		87	84	82
4	97	89	84	79		95	88	83	79		86	82	78		84	80	77		82	79	76
5	92	83	78	73		90	83	77	73		81	76	72		79	75	72		77	74	71
6	87	78	72	68		86	77	72	68		76	71	67		74	70	67		73	69	66
7	83	73	67	63		81	73	67	63		71	66	62		70	66	62		69	65	62
8	79	69	63	59		77	68	63	59		67	62	58		66	62	58		65	61	58
9	75	65	59	55		74	65	59	55		64	58	55		63	58	55		62	58	54
10	71	61	56	52		70	61	55	52		60	55	51		59	55	51		59	54	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	918872
5°	919629
10°	952008
15°	953583
20°	877930
25°	748037
30°	572656
35°	404577
40°	238805
45°	96945
50°	35152
55°	19582
60°	11232
65°	6179
70°	6485
75°	5066
80°	5285
85°	4513

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 96945 cd/sqm



TEST NUMBER: P774760

CATALOG NUMBER: LD6D95BD010-EU6DR6570959035-6LBDP1MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	809.8	9.5
10°-20°	2335.9	27.3
20°-30°	2802.7	32.8
30°-40°	1883.5	22.1
40°-50°	563.8	6.6
50°-60°	99.5	1.2
60°-70°	28.3	0.3
70°-80°	13.9	0.2
80°-90°	4.4	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5948.4	69.6
0°-40°	7831.8	91.7
0°-60°	8495.2	99.5
0°-90°	8541.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8541.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8410	
5°	8385	810
15°	8430	2336
25°	6205	2803
35°	3033	1883
45°	627	564
55°	103	100
65°	24	28
75°	12	14
85°	4	4
90°	0	



TEST NUMBER: P774760

CATALOG NUMBER: LD6D95BD010-EU6DR6570959035-6LBDP1MW

CANDELA DISTRIBUTION (FULL):

	0°
0°	8409.9
2.5°	8445.8
5°	8384.8
7.5°	8511.5
10°	8580.8
12.5°	8564.1
15°	8430.2
17.5°	8102.8
20°	7550.6
22.5°	6900.5
25°	6204.9
27.5°	5419.8
30°	4539.0
32.5°	3740.7
35°	3033.2
37.5°	2334.0
40°	1674.3
42.5°	1093.5
45°	627.4
47.5°	332.2
50°	206.8
52.5°	143.4
55°	102.8
57.5°	74.1
60°	51.4
62.5°	33.5
65°	23.9
67.5°	21.5
70°	20.3
72.5°	15.5
75°	12.0
77.5°	10.8
80°	8.4
82.5°	6.0
85°	3.6
87.5°	2.4
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)