

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774551

Luminaire Tested: LD6D95BD010-EU6DR5070959050-6LBDP1LI

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P774551
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-44)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR5070959050-6LBDP1LI
Description: 6 INCH ROUND DEEP 45° CUTOFF SPECULAR CLEAR TRIM, WITH 50° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 12973.7 lumens
Efficiency: N/A
Efficacy: 130.8 lumens/watt
Spacing Criteria (0/90/45): 0.8 / 0.8 / 0.73
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight

TEST NUMBER: P774551

CATALOG NUMBER: LD6D95BD010-EU6DR5070959050-6LBDP1LI

Luminous Intensity Polar Plot



TEST NUMBER: P774551

CATALOG NUMBER: LD6D95BD010-EU6DR5070959050-6LBDP1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	109	107	112	110	108	106	106	104	102		102	101	99		98
2	109	105	101	98	107	103	100	97	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	90	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	90	87	84		89	85	83		87
5	96	89	84	80	95	88	83	79	86	82	79		85	81	78		83
6	92	84	79	75	91	83	79	75	82	78	74		81	77	74		79
7	88	80	75	71	87	79	74	71	78	74	71		77	73	70		76
8	85	76	71	67	84	76	71	67	75	70	67		74	70	67		73
9	81	73	68	64	80	72	67	64	71	67	64		71	67	64		70
10	78	70	64	61	77	69	64	61	68	64	61		68	64	61		67

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2283976
5°	2260038
10°	2222820
15°	2024047
20°	1684236
25°	1195565
30°	632811
35°	257882
40°	95776
45°	43837
50°	17967
55°	9391
60°	4611
65°	1370
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 43837 cd/sqm

TEST NUMBER: P774551

CATALOG NUMBER: LD6D95BD010-EU6DR5070959050-6LBDP1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1947.7	15.0
10°-20°	4922.2	37.9
20°-30°	4421.5	34.1
30°-40°	1384.3	10.7
40°-50°	242.4	1.9
50°-60°	48.3	0.4
60°-70°	7.3	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	11291.4	87.0
0°-40°	12675.7	97.7
0°-60°	12966.4	99.9
0°-90°	12973.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	12973.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	20904	
5°	20606	###
15°	17894	4922
25°	9917	4421
35°	1933	1384
45°	284	242
55°	49	48
65°	5	7
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P774551

CATALOG NUMBER: LD6D95BD010-EU6DR5070959050-6LBDP1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	20903.9
2.5°	20799.9
5°	20606.1
7.5°	20310.0
10°	20035.1
12.5°	19153.9
15°	17893.7
17.5°	16293.5
20°	14485.2
22.5°	12393.3
25°	9917.1
27.5°	7291.1
30°	5015.8
32.5°	3265.7
35°	1933.4
37.5°	1110.3
40°	671.5
42.5°	437.1
45°	283.7
47.5°	172.7
50°	105.7
52.5°	72.3
55°	49.3
57.5°	33.5
60°	21.1
62.5°	12.3
65°	5.3
67.5°	1.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)