

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P760839

Luminaire Tested: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P760839
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-76)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW
Description: 6 INCH SQAURE SHALLOW CAST MATTE WHITE TRIM, WITH 70° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 4000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1130.5 lumens
Efficiency: N/A
Efficacy: 96.6 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.04
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 11.7
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P760839

CATALOG NUMBER: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW

Luminous Intensity Polar Plot



TEST NUMBER: P760839

CATALOG NUMBER: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	107	105	111	108	106	103	104	102	100		100	99	97		97
2	107	102	97	94	105	100	96	92	97	93	90		94	91	88		91
3	101	94	88	84	99	92	87	83	90	85	82		87	84	81		85
4	95	87	81	76	93	86	80	76	83	78	75		81	77	74		79
5	89	80	74	69	88	79	73	69	78	72	68		76	71	68		74
6	84	75	68	63	83	74	68	63	72	67	63		71	66	62		69
7	80	69	63	58	78	69	62	58	67	62	58		66	61	57		65
8	75	65	58	54	74	64	58	54	63	57	53		62	57	53		61
9	71	61	54	50	70	60	54	50	59	53	50		58	53	49		57
10	67	57	50	46	66	56	50	46	55	50	46		55	50	46		54

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	97493
5°	97252
10°	97045
15°	97019
20°	96065
25°	90248
30°	80442
35°	64144
40°	42589
45°	25465
50°	13190
55°	6934
60°	2447
65°	52
70°	0
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 25465 cd/sqm



TEST NUMBER: P760839

CATALOG NUMBER: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	84.3	7.5
10°-20°	241.9	21.4
20°-30°	341.2	30.2
30°-40°	294.5	26.1
40°-50°	131.9	11.7
50°-60°	34.5	3.1
60°-70°	2.3	0.2
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	667.3	59.0
0°-40°	961.9	85.1
0°-60°	1128.3	99.8
0°-90°	1130.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1130.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	892	
5°	887	84
15°	858	242
25°	749	341
35°	481	295
45°	165	132
55°	36	35
65°	0	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P760839

CATALOG NUMBER: LD6D10D010-EU6DR700210IC9040-6LBCSSQMW

CANDELA DISTRIBUTION (FULL):

	0°
0°	892.3
2.5°	891.3
5°	886.7
7.5°	882.9
10°	874.7
12.5°	867.3
15°	857.7
17.5°	846.6
20°	826.2
22.5°	792.7
25°	748.6
27.5°	697.3
30°	637.6
32.5°	564.6
35°	480.9
37.5°	388.5
40°	298.6
42.5°	226.9
45°	164.8
47.5°	113.6
50°	77.6
52.5°	53.6
55°	36.4
57.5°	22.0
60°	11.2
62.5°	3.6
65°	0.2
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)