

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P761063

Luminaire Tested: LD6D15D010-EU6DR2015309035-6LBSQW1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P761063
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2310-195-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D15D010-EU6DR2015309035-6LBSQW1B
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 20° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3500K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1248.7 lumens
Efficiency: N/A
Efficacy: 79.0 lumens/watt
Spacing Criteria (0/90/45): 0.34 / 0.34 / 0.36
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct

Input Watts (W): 15.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT




Downlight



TEST NUMBER: P761063

CATALOG NUMBER: LD6D15D010-EU6DR2015309035-6LBSQW1B

Luminous Intensity Polar Plot





TEST NUMBER: P761063

CATALOG NUMBER: LD6D15D010-EU6DR2015309035-6LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20							
RC	80				70				50				30				10				0			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																								
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	100	100	100			
1	115	113	111	109	113	111	109	108	107	106	104	103	102	101	100	99	98	97	97	97	97			
2	111	108	105	102	109	106	104	101	103	101	99	100	99	97	98	96	95	94	94	94	94			
3	108	103	100	97	106	102	99	96	100	97	95	97	95	93	95	93	92	91	91	91	91			
4	105	99	96	93	103	98	95	92	96	93	91	95	92	90	93	91	89	88	88	88	88			
5	102	96	92	89	100	95	91	89	94	90	88	92	89	87	91	88	86	85	85	85	85			
6	99	93	89	86	98	92	88	86	91	87	85	90	87	84	88	86	84	83	83	83	83			
7	96	90	86	83	95	89	86	83	88	85	82	87	84	82	86	84	82	81	81	81	81			
8	94	87	83	81	93	87	83	80	86	83	80	85	82	80	84	82	80	79	79	79	79			
9	91	85	81	78	91	85	81	78	84	80	78	83	80	78	82	80	78	77	77	77	77			
10	89	83	79	76	88	82	79	76	82	78	76	81	78	76	81	78	76	75	75	75	75			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	776582
5°	700624
10°	393227
15°	199886
20°	84635
25°	39072
30°	20678
35°	11137
40°	5962
45°	3523
50°	2040
55°	1086
60°	699
65°	491
70°	192
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3523 cd/sqm



TEST NUMBER: P761063

CATALOG NUMBER: LD6D15D010-EU6DR2015309035-6LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	506.1	40.5
10°-20°	498.3	39.9
20°-30°	162.8	13.0
30°-40°	55.4	4.4
40°-50°	18.6	1.5
50°-60°	5.6	0.4
60°-70°	1.9	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1167.1	93.5
0°-40°	1222.5	97.9
0°-60°	1246.8	99.8
0°-90°	1248.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1248.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7108	
5°	6388	506
15°	1767	498
25°	324	163
35°	84	55
45°	23	19
55°	6	6
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P761063

CATALOG NUMBER: LD6D15D010-EU6DR2015309035-6LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	7107.6
0.5°	7107.6
1°	7098.8
1.5°	7081.1
2°	7048.8
2.5°	7005.7
3°	6945.0
3.5°	6860.2
4°	6734.2
4.5°	6581.0
5°	6388.0
5.5°	6134.2
6°	5874.1
6.5°	5576.0
7°	5284.2
7.5°	4942.4
8°	4637.4
8.5°	4330.4
9°	4046.9
9.5°	3786.7
10°	3544.3
12.5°	2545.0
15°	1767.1
17.5°	1154.4
20°	727.9
22.5°	471.5
25°	324.1
27.5°	227.8
30°	163.9
32.5°	117.7
35°	83.5
37.5°	58.2
40°	41.8
42.5°	30.4
45°	22.8
47.5°	17.7
50°	12.0
52.5°	7.6
55°	5.7
57.5°	4.4
60°	3.2
62.5°	2.5
65°	1.9



TEST NUMBER: P761063

CATALOG NUMBER: LD6D15D010-EU6DR2015309035-6LBSQW1B

CANDELA DISTRIBUTION (continued):

	0°
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







67.5°	1.3
70°	0.6



(END OF REPORT)