

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P767927

Luminaire Tested: LD6D55D010-EU6DR2555659050-6LBSQW1B

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P767927
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-4)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D55D010-EU6DR2555659050-6LBSQW1B
Description: 6 INCH SQAURE DEEP 45° CUTOFF SPECULAR BLACK TRIM, WITH 25° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 5000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4684.3 lumens
Efficiency: N/A
Efficacy: 80.5 lumens/watt
Spacing Criteria (0/90/45): 0.42 / 0.42 / 0.45
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 58.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P767927

CATALOG NUMBER: LD6D55D010-EU6DR2555659050-6LBSQW1B

Luminous Intensity Polar Plot



TEST NUMBER: P767927

CATALOG NUMBER: LD6D55D010-EU6DR2555659050-6LBSQW1B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	115	113	111	109	112	110	109	107	106	105	104		103	102	101		99
2	111	107	104	101	109	105	102	100	102	100	98		99	97	96		97
3	107	102	98	95	105	101	97	94	98	95	93		96	93	91		94
4	103	97	93	90	102	96	93	90	94	91	89		93	90	88		91
5	100	93	89	86	98	93	89	86	91	87	85		89	86	84		88
6	97	90	85	82	95	89	85	82	88	84	81		87	83	81		85
7	93	87	82	79	92	86	82	79	85	81	78		84	80	78		83
8	91	84	79	76	90	83	79	76	82	78	76		81	78	75		80
9	88	81	76	73	87	80	76	73	80	76	73		79	75	73		78
10	85	78	74	71	85	78	74	71	77	73	71		76	73	71		76

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	1941170
5°	1807956
10°	1289662
15°	759568
20°	472614
25°	259364
30°	118619
35°	44923
40°	20339
45°	12238
50°	5082
55°	3276
60°	2294
65°	1551
70°	224
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 12238 cd/sqm



TEST NUMBER: P767927

CATALOG NUMBER: LD6D55D010-EU6DR2555659050-6LBSQW1B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1416.7	30.2
10°-20°	1918.8	41.0
20°-30°	1015.4	21.7
30°-40°	250.7	5.4
40°-50°	61.2	1.3
50°-60°	16.1	0.3
60°-70°	5.4	0.1
70°-80°	0.1	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4350.9	92.9
0°-40°	4601.5	98.2
0°-60°	4678.8	99.9
0°-90°	4684.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4684.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	17766	
5°	16484	###
15°	6715	1919
25°	2151	1015
35°	337	251
45°	79	61
55°	17	16
65°	6	5
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P767927

CATALOG NUMBER: LD6D55D010-EU6DR2555659050-6LBSQW1B

CANDELA DISTRIBUTION (FULL):

	0°
0°	17766.4
2.5°	17474.4
5°	16484.2
7.5°	14494.8
10°	11624.2
12.5°	8787.2
15°	6715.0
17.5°	5233.4
20°	4064.7
22.5°	3048.3
25°	2151.4
27.5°	1442.8
30°	940.2
32.5°	572.0
35°	336.8
37.5°	206.1
40°	142.6
42.5°	109.0
45°	79.2
47.5°	47.8
50°	29.9
52.5°	21.7
55°	17.2
57.5°	13.4
60°	10.5
62.5°	8.2
65°	6.0
67.5°	2.2
70°	0.7
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)