

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

Brand: PORTFOLIO

Report Number: P774429

Luminaire Tested: LD6D95BD010-EU6DR4570959030-6LBCSSQMB

Issue Date: 2/2/2024

Test Information

Test Method: LM-79-2019
Report Number: P774429
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-2307-078-36)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 2/2/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PORTFOLIO
Catalog Number: LD6D95BD010-EU6DR4570959030-6LBCSSQMB
Description: 6 INCH SQAURE SHALLOW CAST MATTE BLACK TRIM, WITH 45° OPTIC
Light Source: (1) HIGH LUMEN LED 90CRI / 3000K CCT
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 10980.9 lumens
Efficiency: N/A
Efficacy: 110.7 lumens/watt
Spacing Criteria (0/90/45): 0.75 / 0.75 / 0.69
Luminous Opening: Circular (Dia: 0.35' x H: 0')
CIE Type: Direct


Input Watts (W): 99.2
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT



TEST NUMBER: P774429

CATALOG NUMBER: LD6D95BD010-EU6DR4570959030-6LBCSSQMB

Luminous Intensity Polar Plot



TEST NUMBER: P774429

CATALOG NUMBER: LD6D95BD010-EU6DR4570959030-6LBCSSQMB

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	98	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	79		83
6	92	85	80	76	91	84	79	76	83	78	75		81	77	75		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	67		73
9	82	73	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		68	64	61		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2120642
5°	2060270
10°	1971116
15°	1803993
20°	1431191
25°	893512
30°	492479
35°	221135
40°	87090
45°	41040
50°	19463
55°	10172
60°	5004
65°	1189
70°	479
75°	0
80°	0
85°	0

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 41040 cd/sqm



TEST NUMBER: P774429

CATALOG NUMBER: LD6D95BD010-EU6DR4570959030-6LBCSSQMB

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1765.0	16.1
10°-20°	4343.9	39.6
20°-30°	3439.9	31.3
30°-40°	1145.5	10.4
40°-50°	227.3	2.1
50°-60°	51.6	0.5
60°-70°	7.4	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	9548.8	87.0
0°-40°	10694.3	97.4
0°-60°	10973.3	99.9
0°-90°	10980.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	10980.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	19409	
5°	18785	###
15°	15948	4344
25°	7412	3440
35°	1658	1146
45°	266	227
55°	53	52
65°	5	7
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P774429

CATALOG NUMBER: LD6D95BD010-EU6DR4570959030-6LBCSSQMB

CANDELA DISTRIBUTION (FULL):

0°	
0°	19409.0
2.5°	19282.3
5°	18784.7
7.5°	18374.0
10°	17766.4
12.5°	16957.3
15°	15948.3
17.5°	14430.8
20°	12308.9
22.5°	9780.8
25°	7411.6
27.5°	5427.0
30°	3903.5
32.5°	2654.7
35°	1657.9
37.5°	983.1
40°	610.6
42.5°	401.5
45°	265.6
47.5°	171.0
50°	114.5
52.5°	76.3
55°	53.4
57.5°	35.1
60°	22.9
62.5°	12.2
65°	4.6
67.5°	1.5
70°	1.5
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By 670245859 / DESKTOP-T8S5UU9





— 0°-180°







(END OF REPORT)