

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204685

Luminaire Tested: **LD6B20D010 EU6B10209027 6LBPSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204685
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B20D010 EU6B10209027 6LBPSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH PLASTIC MATTE WHITE TRIM
WATTAGE D010TR-21.86 W DE010-20.46 W D5LT-21.24 W DMX-20.89 W DL2-22.5 W
DL3-21.8 6 W DLE-22.46 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1878.2 lumens
Efficiency: N/A
Efficacy: 90.3 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 20.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204685

CATALOG NUMBER: LD6B20D010 EU6B10209027 6LBPSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204685

CATALOG NUMBER: LD6B20D010 EU6B10209027 6LBPSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	99	107	104	100	97	99	97	94		96	93	91		92
2	101	93	87	82	98	92	86	81	88	83	79		85	81	77		82
3	93	83	75	69	90	81	74	69	78	72	67		76	70	66		73
4	85	74	66	59	83	72	65	59	70	63	58		68	62	57		66
5	78	66	58	51	76	65	57	51	63	56	51		61	55	50		59
6	73	60	51	45	71	59	51	45	57	50	44		55	49	44		54
7	67	54	46	40	66	54	46	40	52	45	40		51	44	39		49
8	63	50	41	36	61	49	41	36	48	41	35		46	40	35		45
9	59	46	38	32	57	45	37	32	44	37	32		43	36	32		42
10	55	42	34	29	54	42	34	29	41	34	29		40	33	29		39

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204685

CATALOG NUMBER: LD6B20D010 EU6B10209027 6LBPSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	71.7	3.8
10°-20°	204.4	10.9
20°-30°	307.8	16.4
30°-40°	366.3	19.5
40°-50°	365.6	19.5
50°-60°	297.3	15.8
60°-70°	182.9	9.7
70°-80°	70.8	3.8
80°-90°	11.4	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	583.9	31.1
0°-40°	950.2	50.6
0°-60°	1613.1	85.9
0°-90°	1878.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1878.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	757	
5°	754	72
15°	726	204
25°	670	308
35°	586	366
45°	475	366
55°	333	297
65°	184	183
75°	64	71
85°	9	11
90°	0	



TEST NUMBER: P204685

CATALOG NUMBER: LD6B20D010 EU6B10209027 6LBPSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	756.7
2.5°	757.9
5°	754.5
7.5°	750.1
10°	744.5
12.5°	734.5
15°	725.6
17.5°	712.2
20°	697.8
22.5°	684.4
25°	669.9
27.5°	649.9
30°	629.9
32.5°	611.0
35°	586.5
37.5°	559.8
40°	535.3
42.5°	505.2
45°	475.2
47.5°	442.9
50°	408.4
52.5°	372.8
55°	332.7
57.5°	293.8
60°	256.0
62.5°	219.2
65°	183.6
67.5°	150.2
70°	119.1
72.5°	90.1
75°	64.5
77.5°	42.3
80°	25.6
82.5°	15.6
85°	8.9
87.5°	4.5
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)