

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204799

Luminaire Tested: **LD6B30D010 EU6B30508050 6LBCSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204799
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B30D010 EU6B30508050 6LBCSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE WHITE TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3360.1 lumens
Efficiency: N/A
Efficacy: 120.0 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204799

CATALOG NUMBER: LD6B30D010 EU6B30508050 6LBCSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204799

CATALOG NUMBER: LD6B30D010 EU6B30508050 6LBCSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	99	108	104	100	97	100	97	94		96	93	91		92
2	101	94	87	82	99	92	86	81	88	84	79		85	81	78		82
3	93	83	75	70	90	81	74	69	79	73	68		76	71	67		73
4	85	74	66	60	83	73	65	59	70	64	58		68	62	58		66
5	79	66	58	52	77	65	57	51	63	56	51		61	55	50		60
6	73	60	52	45	71	59	51	45	57	50	45		56	49	44		54
7	68	55	46	40	66	54	46	40	52	45	40		51	44	40		50
8	63	50	42	36	61	49	41	36	48	41	36		47	40	36		46
9	59	46	38	33	57	45	38	32	44	37	32		43	37	32		42
10	55	42	35	30	54	42	34	30	41	34	29		40	34	29		39

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204799

CATALOG NUMBER: LD6B30D010 EU6B30508050 6LBCSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	130.0	3.9
10°-20°	370.2	11.0
20°-30°	556.9	16.6
30°-40°	659.9	19.6
40°-50°	656.7	19.5
50°-60°	529.4	15.8
60°-70°	320.3	9.5
70°-80°	118.9	3.5
80°-90°	17.7	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1057.1	31.5
0°-40°	1717.0	51.1
0°-60°	2903.2	86.4
0°-90°	3360.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3360.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1372	
5°	1366	130
15°	1311	370
25°	1210	557
35°	1057	660
45°	855	657
55°	590	529
65°	322	320
75°	108	119
85°	14	18
90°	0	



TEST NUMBER: P204799

CATALOG NUMBER: LD6B30D010 EU6B30508050 6LBCSMW1

CANDELA DISTRIBUTION (FULL):

0°	
0°	1372.4
2.5°	1372.4
5°	1366.3
7.5°	1362.2
10°	1350.0
12.5°	1329.6
15°	1311.3
17.5°	1290.9
20°	1266.5
22.5°	1242.1
25°	1209.5
27.5°	1174.9
30°	1136.2
32.5°	1099.5
35°	1056.8
37.5°	1012.0
40°	959.0
42.5°	908.1
45°	855.2
47.5°	796.1
50°	731.0
52.5°	663.8
55°	590.5
57.5°	525.3
60°	452.0
62.5°	386.9
65°	321.7
67.5°	260.6
70°	203.6
72.5°	152.7
75°	107.9
77.5°	69.2
80°	40.7
82.5°	24.4
85°	14.3
87.5°	6.1
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)