

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204702

Luminaire Tested: **LD6B30D010 EU6B30509050 6LBPSMW1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204702
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B30D010 EU6B30509050 6LBPSMW1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH PLASTIC MATTE WHITE TRIM
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W
DL3-29.67 W DLE-29.73 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2797.0 lumens
Efficiency: N/A
Efficacy: 99.9 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.34
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 28
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204702

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBPSMW1

Luminous Intensity Polar Plot





TEST NUMBER: P204702

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBPSMW1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	110	106	102	99	107	104	100	97	99	97	94		96	93	91		92
2	101	93	87	82	98	92	86	81	88	83	79		85	81	77		82
3	93	83	75	69	90	81	74	69	78	72	67		76	70	66		73
4	85	74	66	59	83	72	65	59	70	63	58		68	62	57		66
5	78	66	58	51	76	65	57	51	63	56	51		61	55	50		59
6	73	60	51	45	71	59	51	45	57	50	44		55	49	44		54
7	67	54	46	40	66	54	46	40	52	45	40		51	44	39		49
8	63	50	41	36	61	49	41	36	48	41	35		46	40	35		45
9	59	46	38	32	57	45	37	32	44	37	32		43	36	32		42
10	55	42	34	29	54	42	34	29	41	34	29		40	33	29		39

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204702

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBPSMW1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	106.8	3.8
10°-20°	304.4	10.9
20°-30°	458.4	16.4
30°-40°	545.4	19.5
40°-50°	544.5	19.5
50°-60°	442.8	15.8
60°-70°	272.4	9.7
70°-80°	105.5	3.8
80°-90°	16.9	0.6
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	869.5	31.1
0°-40°	1415.0	50.6
0°-60°	2402.2	85.9
0°-90°	2797.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2797.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1127	
5°	1124	107
15°	1080	304
25°	998	458
35°	873	545
45°	708	544
55°	496	443
65°	273	272
75°	96	106
85°	13	17
90°	0	



TEST NUMBER: P204702

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBPSMW1

CANDELA DISTRIBUTION (FULL):

	0°
0°	1126.9
2.5°	1128.6
5°	1123.6
7.5°	1117.0
10°	1108.7
12.5°	1093.8
15°	1080.5
17.5°	1060.7
20°	1039.1
22.5°	1019.2
25°	997.7
27.5°	967.8
30°	938.0
32.5°	909.8
35°	873.4
37.5°	833.6
40°	797.1
42.5°	752.4
45°	707.7
47.5°	659.6
50°	608.2
52.5°	555.2
55°	495.5
57.5°	437.5
60°	381.2
62.5°	326.5
65°	273.4
67.5°	223.7
70°	177.3
72.5°	134.2
75°	96.1
77.5°	63.0
80°	38.1
82.5°	23.2
85°	13.3
87.5°	6.6
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)