

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205213

Luminaire Tested: **LD6B30D010 EU6B30509050 6LBWLI1**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-41-14  
Report Number: P205213  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)  
Test Lab: INNOVATION CENTER-P3  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: io LED  
Catalog Number: LD6B30D010 EU6B30509050 6LBWLI1  
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT  
WIDE DISTRIBUTION WITH SPECULAR CLEAR TRIM  
WATTAGE D010TR-27.4 W DE010-27.95 W D5LT-27.65 W DMX-27.73 W DL2-29.56 W  
DL3-29.67 W DLE-29.73 W  
Light Source: HIGH LUMEN LED  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 2602.5 lumens  
Efficiency: N/A  
Efficacy: 92.9 lumens/watt  
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.18  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 28  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P205213

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBWLI1

### Luminous Intensity Polar Plot






TEST NUMBER: P205213

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBWLI1

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 |
| 1   | 113 | 110 | 107 | 104 | 110 | 107 | 105 | 103 | 103 | 101 | 99  |  | 100 | 98  | 97  |  | 96  |
| 2   | 106 | 101 | 96  | 92  | 104 | 99  | 95  | 91  | 95  | 92  | 89  |  | 92  | 90  | 87  |  | 90  |
| 3   | 100 | 92  | 87  | 82  | 97  | 91  | 86  | 81  | 88  | 84  | 80  |  | 86  | 82  | 79  |  | 83  |
| 4   | 93  | 85  | 78  | 73  | 92  | 84  | 78  | 73  | 81  | 76  | 72  |  | 79  | 75  | 71  |  | 77  |
| 5   | 88  | 78  | 71  | 66  | 86  | 77  | 71  | 66  | 75  | 70  | 65  |  | 73  | 69  | 65  |  | 72  |
| 6   | 82  | 72  | 65  | 60  | 81  | 71  | 65  | 60  | 70  | 64  | 59  |  | 68  | 63  | 59  |  | 67  |
| 7   | 77  | 67  | 60  | 55  | 76  | 66  | 59  | 55  | 65  | 59  | 54  |  | 63  | 58  | 54  |  | 62  |
| 8   | 73  | 62  | 55  | 50  | 71  | 61  | 55  | 50  | 60  | 54  | 50  |  | 59  | 54  | 50  |  | 58  |
| 9   | 69  | 57  | 51  | 46  | 67  | 57  | 50  | 46  | 56  | 50  | 46  |  | 55  | 50  | 46  |  | 54  |
| 10  | 65  | 54  | 47  | 43  | 64  | 53  | 47  | 42  | 52  | 46  | 42  |  | 51  | 46  | 42  |  | 51  |

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P205213

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBWLI1

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 156.8  | 6.0       |
| 10°-20°   | 471.4  | 18.1      |
| 20°-30°   | 710.6  | 27.3      |
| 30°-40°   | 727.3  | 27.9      |
| 40°-50°   | 423.7  | 16.3      |
| 50°-60°   | 97.4   | 3.7       |
| 60°-70°   | 12.0   | 0.5       |
| 70°-80°   | 3.1    | 0.1       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 1338.9 | 51.4      |
| 0°-40°    | 2066.2 | 79.4      |
| 0°-60°    | 2587.3 | 99.4      |
| 0°-90°    | 2602.5 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 2602.5 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°   | Flux |
|-----|------|------|
| 0°  | 1626 |      |
| 5°  | 1635 | 157  |
| 15° | 1670 | 471  |
| 25° | 1558 | 711  |
| 35° | 1180 | 727  |
| 45° | 546  | 424  |
| 55° | 94   | 97   |
| 65° | 9    | 12   |
| 75° | 3    | 3    |
| 85° | 0    | 0    |
| 90° | 0    |      |



TEST NUMBER: P205213

CATALOG NUMBER: LD6B30D010 EU6B30509050 6LBWLI1

**CANDELA DISTRIBUTION (FULL):**

| 0°    |        |
|-------|--------|
| 0°    | 1625.8 |
| 2.5°  | 1622.8 |
| 5°    | 1634.6 |
| 7.5°  | 1646.4 |
| 10°   | 1661.2 |
| 12.5° | 1664.1 |
| 15°   | 1670.0 |
| 17.5° | 1664.1 |
| 20°   | 1649.4 |
| 22.5° | 1602.1 |
| 25°   | 1557.9 |
| 27.5° | 1487.1 |
| 30°   | 1395.6 |
| 32.5° | 1301.2 |
| 35°   | 1180.2 |
| 37.5° | 1044.5 |
| 40°   | 894.0  |
| 42.5° | 725.8  |
| 45°   | 545.9  |
| 47.5° | 380.6  |
| 50°   | 250.8  |
| 52.5° | 159.3  |
| 55°   | 94.4   |
| 57.5° | 50.2   |
| 60°   | 26.6   |
| 62.5° | 14.8   |
| 65°   | 8.9    |
| 67.5° | 8.9    |
| 70°   | 5.9    |
| 72.5° | 3.0    |
| 75°   | 3.0    |
| 77.5° | 3.0    |
| 80°   | 0.0    |
| 82.5° | 0.0    |
| 85°   | 0.0    |
| 87.5° | 0.0    |
| 90°   | 0.0    |



Report Generated By E9808895 / USPTCWHP6082093







— 0°-180°







(END OF REPORT)