

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P202968

Luminaire Tested: **LD6B50D010TE EU6B30508040 6LBWGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P202968
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B50D010TE EU6B30508040 6LBWGPH1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTIONWITH GRAPHITE HAZE TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3685.4 lumens
Efficiency: N/A
Efficacy: 62.7 lumens/watt
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.11
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P202968

CATALOG NUMBER: LD6B50D010TE EU6B30508040 6LBWGP1

Luminous Intensity Polar Plot





TEST NUMBER: P202968

CATALOG NUMBER: LD6B50D010TE EU6B30508040 6LBWGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89
3	99	91	85	81	97	90	84	80	87	82	79		85	81	77		82
4	93	84	77	72	91	82	76	72	80	75	71		78	74	70		76
5	87	77	70	65	85	76	69	65	74	68	64		72	67	63		71
6	81	71	64	59	80	70	63	59	68	62	58		67	62	58		65
7	76	65	58	53	75	65	58	53	63	57	53		62	57	53		61
8	72	61	54	49	70	60	53	49	59	53	49		58	52	48		57
9	68	57	50	45	66	56	49	45	55	49	45		54	48	45		53
10	64	53	46	42	63	52	46	42	51	45	41		51	45	41		50

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P202968

CATALOG NUMBER: LD6B50D010TE EU6B30508040 6LBWGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	236.0	6.4
10°-20°	661.7	18.0
20°-30°	946.7	25.7
30°-40°	943.6	25.6
40°-50°	601.0	16.3
50°-60°	221.6	6.0
60°-70°	55.4	1.5
70°-80°	16.7	0.5
80°-90°	2.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1844.4	50.0
0°-40°	2788.1	75.7
0°-60°	3610.7	98.0
0°-90°	3685.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3685.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2505	
5°	2492	236
15°	2353	662
25°	2067	947
35°	1535	944
45°	774	601
55°	235	222
65°	51	55
75°	13	17
85°	0	3
90°	0	



TEST NUMBER: P202968

CATALOG NUMBER: LD6B50D010TE EU6B30508040 6LBWGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2504.8
2.5°	2504.8
5°	2492.1
7.5°	2466.8
10°	2435.1
12.5°	2397.0
15°	2352.6
17.5°	2295.6
20°	2232.2
22.5°	2162.4
25°	2067.3
27.5°	1965.8
30°	1832.6
32.5°	1693.1
35°	1534.6
37.5°	1344.4
40°	1147.8
42.5°	957.5
45°	773.6
47.5°	608.8
50°	456.6
52.5°	336.1
55°	234.6
57.5°	152.2
60°	101.5
62.5°	69.8
65°	50.7
67.5°	38.0
70°	31.7
72.5°	19.0
75°	12.7
77.5°	12.7
80°	6.3
82.5°	6.3
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)