

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P204928

Luminaire Tested: **LD6B50D010TE EU6B30508050 6LBCSMB1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204928
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B50D010TE EU6B30508050 6LBCSMB1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH CAST MATTE BLACK TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5135.3 lumens
Efficiency: N/A
Efficacy: 87.4 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.33
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 58.77
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204928

CATALOG NUMBER: LD6B50D010TE EU6B30508050 6LBSCMB1

Luminous Intensity Polar Plot




TEST NUMBER: P204928
CATALOG NUMBER: LD6B50D010TE EU6B30508050 6LBCSMB1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88		
2	102	95	89	84	99	93	87	83	89	85	81	86	82	79	83	80	77	75		
3	93	84	77	71	91	83	76	70	80	74	69	77	72	68	74	70	67	65		
4	86	75	67	61	84	74	66	61	71	65	60	69	63	59	67	62	58	56		
5	79	67	59	53	77	66	59	53	64	57	52	62	56	52	61	55	51	49		
6	74	61	53	47	72	60	52	46	58	51	46	57	50	46	55	50	45	43		
7	68	55	47	41	67	55	47	41	53	46	41	52	45	41	50	45	40	39		
8	64	51	43	37	62	50	42	37	49	42	37	48	41	37	46	41	36	35		
9	60	47	39	33	58	46	39	33	45	38	33	44	38	33	43	37	33	31		
10	56	43	35	30	55	43	35	30	42	35	30	41	34	30	40	34	30	28		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204928

CATALOG NUMBER: LD6B50D010TE EU6B30508050 6LBCSMB1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	205.1	4.0
10°-20°	584.3	11.4
20°-30°	878.4	17.1
30°-40°	1042.2	20.3
40°-50°	1031.4	20.1
50°-60°	810.1	15.8
60°-70°	454.2	8.8
70°-80°	127.5	2.5
80°-90°	2.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1667.8	32.5
0°-40°	2710.0	52.8
0°-60°	4551.5	88.6
0°-90°	5135.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5135.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2168	
5°	2165	205
15°	2073	584
25°	1907	878
35°	1671	1042
45°	1344	1031
55°	913	810
65°	453	454
75°	110	128
85°	0	2
90°	0	



TEST NUMBER: P204928

CATALOG NUMBER: LD6B50D010TE EU6B30508050 6LBCSMB1

CANDELA DISTRIBUTION (FULL):

	0°
0°	2168.4
2.5°	2161.1
5°	2164.7
7.5°	2146.3
10°	2124.2
12.5°	2098.5
15°	2072.7
17.5°	2039.6
20°	1995.4
22.5°	1951.2
25°	1907.0
27.5°	1859.2
30°	1796.6
32.5°	1734.0
35°	1671.4
37.5°	1597.8
40°	1513.1
42.5°	1432.1
45°	1343.8
47.5°	1244.4
50°	1141.3
52.5°	1023.5
55°	913.0
57.5°	787.8
60°	670.0
62.5°	563.3
65°	452.8
67.5°	357.1
70°	265.1
72.5°	180.4
75°	110.4
77.5°	55.2
80°	14.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)