

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P205452

Luminaire Tested: **LD6B60D010TE EU6B60709030 6LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205452
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6B60D010TE EU6B60709030 6LBSLI1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
SINGLE DRIVER D010TE
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5498.6 lumens
Efficiency: N/A
Efficacy: 88.0 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 62.48
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205452

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205452

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20
RC	80					70					50					30					10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10
RCR																					
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102
1	111	107	104	101		109	105	102	99		101	99	96		97	95	93		94	92	91
2	103	96	91	86		100	94	89	85		91	87	83		88	84	81		85	82	79
3	95	86	79	74		93	85	78	73		82	76	72		79	75	71		77	73	70
4	88	78	70	64		86	77	69	64		74	68	63		72	67	62		70	65	62
5	82	71	63	57		80	70	62	57		67	61	56		66	60	55		64	59	55
6	76	64	56	51		74	63	56	51		62	55	50		60	54	50		59	53	49
7	71	59	51	46		70	58	51	45		57	50	45		55	49	45		54	49	45
8	67	54	47	41		65	54	46	41		52	46	41		51	45	41		50	45	41
9	63	50	43	38		61	50	43	38		49	42	38		48	42	37		47	41	37
10	59	47	40	35		58	46	39	35		45	39	35		45	39	34		44	38	34

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205452

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	319.7	5.8
10°-20°	814.0	14.8
20°-30°	1038.0	18.9
30°-40°	1076.5	19.6
40°-50°	991.9	18.0
50°-60°	746.1	13.6
60°-70°	402.8	7.3
70°-80°	108.1	2.0
80°-90°	1.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2171.7	39.5
0°-40°	3248.2	59.1
0°-60°	4986.2	90.7
0°-90°	5498.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5498.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3470	
5°	3417	320
15°	2903	814
25°	2255	1038
35°	1717	1076
45°	1291	992
55°	835	746
65°	403	403
75°	94	108
85°	0	2
90°	0	



TEST NUMBER: P205452

CATALOG NUMBER: LD6B60D010TE EU6B60709030 6LBSLI1

CANDELA DISTRIBUTION (FULL):

0°	
0°	3469.8
2.5°	3458.2
5°	3417.3
7.5°	3341.3
10°	3207.0
12.5°	3072.6
15°	2903.2
17.5°	2745.5
20°	2581.9
22.5°	2412.5
25°	2254.8
27.5°	2102.9
30°	1962.7
32.5°	1834.2
35°	1717.4
37.5°	1606.4
40°	1501.3
42.5°	1390.3
45°	1291.0
47.5°	1180.0
50°	1069.0
52.5°	952.2
55°	835.3
57.5°	718.5
60°	607.5
62.5°	502.4
65°	403.1
67.5°	309.6
70°	227.8
72.5°	157.7
75°	93.5
77.5°	40.9
80°	11.7
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)