

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P135349

Luminaire Tested: **LD6A20D010TE ERM6A20930 6LM1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P135349
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P23398)
Test Lab: INNOVATION CENTER P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6A20D010TE ERM6A20930 6LM1LI
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
MEDIUM DISTRIBUTION WITH SPECULAR CLEAR TRIM
Light Source: (1) HIGH LUMEN LED 3000K
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2256.3 lumens
Efficiency: N/A
Efficacy: 68.8 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.8
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 32.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P135349

CATALOG NUMBER: LD6A20D010TE ERM6A20930 6LM1LI

Luminous Intensity Polar Plot





TEST NUMBER: P135349

CATALOG NUMBER: LD6A20D010TE ERM6A20930 6LM1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	114	111	109	107	112	109	107	105	105	104	102	101	100	99	98	97	96	94		
2	109	104	101	98	107	103	99	96	99	97	94	97	94	92	94	92	90	89		
3	104	98	93	90	102	97	93	89	94	91	88	92	89	86	90	87	85	84		
4	99	92	87	83	98	91	87	83	89	85	82	87	84	81	85	82	80	79		
5	95	87	82	78	93	86	81	77	84	80	77	83	79	76	81	78	75	74		
6	91	82	77	73	89	82	76	73	80	76	72	79	75	72	78	74	71	70		
7	87	78	72	69	85	77	72	68	76	71	68	75	71	68	74	70	67	66		
8	83	74	69	65	82	73	68	65	72	68	64	71	67	64	70	67	64	63		
9	79	70	65	61	78	70	65	61	69	64	61	68	64	61	67	63	61	59		
10	76	67	62	58	75	67	61	58	66	61	58	65	61	58	64	60	57	56		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	202983
5°	205952
10°	207015
15°	188355
20°	153477
25°	119927
30°	86422
35°	46170
40°	16062
45°	4355
50°	1391
55°	694
60°	391
65°	247
70°	305
75°	403
80°	0
85°	0



TEST NUMBER: P135349

CATALOG NUMBER: LD6A20D010TE ERM6A20930 6LM1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	300.1	13.3
10°-20°	763.8	33.9
20°-30°	759.3	33.7
30°-40°	373.8	16.6
40°-50°	50.3	2.2
50°-60°	5.9	0.3
60°-70°	2.1	0.1
70°-80°	1.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1823.1	80.8
0°-40°	2197.0	97.4
0°-60°	2253.1	99.9
0°-90°	2256.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2256.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3111	
5°	3145	300
15°	2789	764
25°	1666	759
35°	580	374
45°	47	50
55°	6	6
65°	2	2
75°	2	1
85°	0	0
90°	0	



TEST NUMBER: P135349

CATALOG NUMBER: LD6A20D010TE ERM6A20930 6LM1LI

CANDELA DISTRIBUTION (FULL):

	0°
0°	3111.3
2.5°	3109.7
5°	3144.8
7.5°	3167.5
10°	3124.9
12.5°	2998.6
15°	2788.7
17.5°	2513.4
20°	2210.6
22.5°	1926.1
25°	1666.0
27.5°	1413.3
30°	1147.2
32.5°	861.1
35°	579.7
37.5°	348.4
40°	188.6
42.5°	97.4
45°	47.2
47.5°	22.9
50°	13.7
52.5°	7.7
55°	6.1
57.5°	4.6
60°	3.0
62.5°	3.0
65°	1.6
67.5°	1.6
70°	1.6
72.5°	1.6
75°	1.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)