

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P135229

Luminaire Tested: **LD6A20D010TE ERN6A20930 6LN1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P135229
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P23370)
Test Lab: INNOVATION CENTER P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6A20D010TE ERN6A20930 6LN1H
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
Light Source: (1) HIGH LUMEN LED 3000K
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1877.2 lumens
Efficiency: N/A
Efficacy: 57.2 lumens/watt
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.84
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 32.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P135229

CATALOG NUMBER: LD6A20D010TE ERN6A20930 6LN1H

Luminous Intensity Polar Plot





TEST NUMBER: P135229

CATALOG NUMBER: LD6A20D010TE ERN6A20930 6LN1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87
4	97	89	84	80	95	88	83	79	86	82	78		84	80	77		82
5	92	84	78	73	90	83	77	73	81	76	72		79	75	72		78
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73
7	83	74	68	63	82	73	67	63	72	67	63		71	66	63		69
8	79	69	63	59	78	69	63	59	68	63	59		67	62	59		66
9	75	66	60	56	74	65	59	56	64	59	55		63	59	55		62
10	72	62	56	52	71	62	56	52	61	56	52		60	55	52		59

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	161529
5°	156259
10°	139304
15°	121414
20°	105148
25°	90219
30°	75733
35°	53147
40°	27662
45°	13157
50°	6902
55°	3742
60°	2570
65°	1698
70°	1240
75°	1109
80°	827
85°	0



TEST NUMBER: P135229

CATALOG NUMBER: LD6A20D010TE ERN6A20930 6LN1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	218.5	11.6
10°-20°	502.3	26.8
20°-30°	574.8	30.6
30°-40°	409.5	21.8
40°-50°	123.8	6.6
50°-60°	32.1	1.7
60°-70°	11.9	0.6
70°-80°	4.0	0.2
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1295.5	69.0
0°-40°	1705.0	90.8
0°-60°	1860.9	99.1
0°-90°	1877.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1877.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2476	
5°	2386	218
15°	1798	502
25°	1253	575
35°	667	410
45°	143	124
55°	33	32
65°	11	12
75°	4	4
85°	0	0
90°	0	



TEST NUMBER: P135229

CATALOG NUMBER: LD6A20D010TE ERN6A20930 6LN1H

CANDELA DISTRIBUTION (FULL):

	0°
0°	2475.9
2.5°	2447.4
5°	2386.0
7.5°	2263.0
10°	2102.8
12.5°	1942.6
15°	1797.6
17.5°	1657.2
20°	1514.5
22.5°	1380.6
25°	1253.3
27.5°	1132.6
30°	1005.3
32.5°	851.7
35°	667.3
37.5°	478.5
40°	324.8
42.5°	215.1
45°	142.6
47.5°	98.7
50°	68.0
52.5°	43.9
55°	32.9
57.5°	24.2
60°	19.7
62.5°	15.4
65°	11.0
67.5°	8.8
70°	6.5
72.5°	4.4
75°	4.4
77.5°	2.2
80°	2.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)