

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P136190

Luminaire Tested: **LD6A20D010TE ERW6A20935 6LW1H**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P136190
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P23374)
Test Lab: INNOVATION CENTER P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6A20D010TE ERW6A20935 6LW1H
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH SEMI-SPECULAR CLEAR TRIM
Light Source: (1) HIGH LUMEN LED 3500K
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2191.6 lumens
Efficiency: N/A
Efficacy: 66.8 lumens/watt
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.09
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 32.8
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P136190

CATALOG NUMBER: LD6A20D010TE ERW6A20935 6LW1H

Luminous Intensity Polar Plot





TEST NUMBER: P136190

CATALOG NUMBER: LD6A20D010TE ERW6A20935 6LW1H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	112	109	106	104	110	107	105	102	103	101	99	99	98	96	96	94	93	91		
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83		
3	99	91	86	81	97	90	85	80	87	83	79	85	81	78	82	79	76	75		
4	93	84	77	72	91	83	77	72	80	75	71	78	74	70	76	73	69	68		
5	87	77	70	65	85	76	70	65	74	69	64	72	68	64	71	67	63	61		
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56		
7	77	66	59	54	75	65	58	54	64	58	53	62	57	53	61	56	53	51		
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47		
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	49	45	43		
10	64	53	46	42	63	53	46	42	52	46	42	51	46	42	50	45	42	40		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	98552
5°	98300
10°	97377
15°	96693
20°	94741
25°	91162
30°	84396
35°	71879
40°	55043
45°	38880
50°	26237
55°	16607
60°	9682
65°	4446
70°	2747
75°	1815
80°	902
85°	0



TEST NUMBER: P136190

CATALOG NUMBER: LD6A20D010TE ERW6A20935 6LW1H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	142.3	6.5
10°-20°	402.6	18.4
20°-30°	578.7	26.4
30°-40°	556.6	25.4
40°-50°	331.4	15.1
50°-60°	136.6	6.2
60°-70°	34.4	1.6
70°-80°	7.9	0.4
80°-90°	1.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1123.7	51.3
0°-40°	1680.2	76.7
0°-60°	2148.3	98.0
0°-90°	2191.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2191.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1511	
5°	1501	142
15°	1432	403
25°	1266	579
35°	902	557
45°	421	331
55°	146	137
65°	29	34
75°	7	8
85°	0	1
90°	0	



TEST NUMBER: P136190

CATALOG NUMBER: LD6A20D010TE ERW6A20935 6LW1H

CANDELA DISTRIBUTION (FULL):

0°	
0°	1510.6
2.5°	1503.4
5°	1501.0
7.5°	1489.0
10°	1469.9
12.5°	1450.8
15°	1431.6
17.5°	1402.8
20°	1364.6
22.5°	1319.0
25°	1266.4
27.5°	1201.7
30°	1120.3
32.5°	1019.8
35°	902.5
37.5°	775.7
40°	646.3
42.5°	526.6
45°	421.4
47.5°	332.7
50°	258.5
52.5°	198.7
55°	146.0
57.5°	105.3
60°	74.2
62.5°	47.9
65°	28.8
67.5°	19.2
70°	14.4
72.5°	9.6
75°	7.2
77.5°	4.8
80°	2.4
82.5°	2.4
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)