

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: io LED

Report Number: P133515

Luminaire Tested: **LD6A20D010TE ERN6A20940 6LN1LI**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P133515
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P23397)
Test Lab: INNOVATION CENTER P2
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: io LED
Catalog Number: LD6A20D010TE ERN6A20940 6LN1LI
Description: PORTFOLIO 6 INCH 50 DEGREE CUTOFF RECESSED DOWNLIGHT
NARROW DISTRIBUTION WITH SPECULAR CLEAR TRIM
Light Source: (1) HIGH LUMEN LED 4000K
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2266.3 lumens
Efficiency: N/A
Efficacy: 69.1 lumens/watt
Spacing Criteria (0/90/45): 0.41 / 0.41 / 0.49
Luminous Opening: Circular (Dia: 0.46' x H: 0')
CIE Type: Direct


Input Watts (W): 32.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P133515

CATALOG NUMBER: LD6A20D010TE ERN6A20940 6LN1LI

Luminous Intensity Polar Plot





TEST NUMBER: P133515

CATALOG NUMBER: LD6A20D010TE ERN6A20940 6LN1LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	114	112	110	108	112	110	108	106	106	104	103		102	101	100		98
2	109	105	102	99	107	103	100	97	100	98	95		97	95	93		95
3	105	99	95	91	103	98	94	91	95	92	89		93	90	88		91
4	100	94	89	85	99	93	88	85	91	87	84		89	86	83		87
5	96	89	84	80	95	88	83	80	86	82	79		85	81	78		83
6	92	85	79	76	91	84	79	75	82	78	75		81	77	74		80
7	89	81	75	72	87	80	75	72	79	74	71		78	74	71		77
8	85	77	72	68	84	76	71	68	75	71	68		74	70	68		74
9	82	74	68	65	81	73	68	65	72	68	65		71	67	64		71
10	79	70	65	62	78	70	65	62	69	65	62		69	65	62		68

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	430934
5°	374039
10°	261729
15°	178325
20°	125768
25°	92623
30°	71047
35°	46488
40°	20184
45°	6458
50°	1939
55°	546
60°	418
65°	247
70°	305
75°	0
80°	0
85°	0



TEST NUMBER: P133515

CATALOG NUMBER: LD6A20D010TE ERN6A20940 6LN1LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	487.5	21.5
10°-20°	743.6	32.8
20°-30°	599.8	26.5
30°-40°	359.0	15.8
40°-50°	68.8	3.0
50°-60°	5.6	0.2
60°-70°	1.8	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1830.9	80.8
0°-40°	2189.9	96.6
0°-60°	2264.3	99.9
0°-90°	2266.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2266.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6605	
5°	5711	488
15°	2640	744
25°	1287	600
35°	584	359
45°	70	69
55°	5	6
65°	2	2
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P133515

CATALOG NUMBER: LD6A20D010TE ERN6A20940 6LN1LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	6605.3
2.5°	6358.8
5°	5711.4
7.5°	4835.1
10°	3950.8
12.5°	3211.1
15°	2640.2
17.5°	2188.5
20°	1811.5
22.5°	1518.9
25°	1286.7
27.5°	1100.6
30°	943.1
32.5°	776.1
35°	583.7
37.5°	392.9
40°	237.0
42.5°	132.0
45°	70.0
47.5°	36.6
50°	19.1
52.5°	6.4
55°	4.8
57.5°	3.2
60°	3.2
62.5°	1.6
65°	1.6
67.5°	1.6
70°	1.6
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)