

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P202805

Luminaire Tested: **LE_6B10D010 EC6B10209035 6LBWWH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P202805
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B10D010 EC6B10209035 6LBWWH1
Description: PORTFOLIO 6 INCH 60 DEGREE CUTOFF RECESSED DOWNLIGHT
WIDE DISTRIBUTION WITH WHEAT TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1052.9 lumens
Efficiency: N/A
Efficacy: 106.4 lumens/watt
Spacing Criteria (0/90/45): 1.23 / 1.23 / 1.18
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P202805

CATALOG NUMBER: LE_6B10D010 EC6B10209035 6LBWWH1

Luminous Intensity Polar Plot






TEST NUMBER: P202805

CATALOG NUMBER: LE_6B10D010 EC6B10209035 6LBWWH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20				20
RC	80				70					50					30				10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30
RCR																			
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100	
1	113	109	107	104	110	107	105	102	103	101	99	99	98	96	96	95	93	92	
2	106	100	96	92	104	98	94	91	95	92	89	92	89	87	89	87	85	83	
3	99	92	86	81	97	90	85	81	88	83	79	85	81	78	83	80	77	75	
4	93	84	78	73	91	83	77	72	81	76	71	79	74	71	77	73	70	68	
5	87	77	71	66	85	76	70	65	75	69	65	73	68	64	71	67	63	62	
6	82	71	64	59	80	71	64	59	69	63	59	67	62	58	66	61	58	56	
7	77	66	59	54	75	65	59	54	64	58	54	63	57	53	61	57	53	51	
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47	
9	68	57	50	45	67	56	50	45	55	49	45	54	49	45	53	48	45	43	
10	64	53	46	42	63	53	46	42	52	46	42	51	45	42	50	45	41	40	

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P202805

CATALOG NUMBER: LE_6B10D010 EC6B10209035 6LBWWH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	62.9	6.0
10°-20°	186.9	17.8
20°-30°	281.4	26.7
30°-40°	287.7	27.3
40°-50°	174.8	16.6
50°-60°	49.2	4.7
60°-70°	7.4	0.7
70°-80°	2.4	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	531.2	50.4
0°-40°	818.9	77.8
0°-60°	1042.9	99.0
0°-90°	1052.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1052.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	654	
5°	657	63
15°	662	187
25°	614	281
35°	466	288
45°	225	175
55°	49	49
65°	7	7
75°	3	2
85°	0	0
90°	0	



TEST NUMBER: P202805

CATALOG NUMBER: LE_6B10D010 EC6B10209035 6LBWWH1

CANDELA DISTRIBUTION (FULL):

0°	
0°	654.0
2.5°	654.0
5°	656.6
7.5°	660.6
10°	660.6
12.5°	663.2
15°	661.9
17.5°	659.2
20°	650.0
22.5°	636.9
25°	614.4
27.5°	589.2
30°	554.9
32.5°	514.0
35°	466.4
37.5°	413.5
40°	352.8
42.5°	289.4
45°	224.6
47.5°	166.5
50°	117.6
52.5°	79.2
55°	48.9
57.5°	29.1
60°	14.5
62.5°	9.2
65°	6.6
67.5°	5.2
70°	4.0
72.5°	2.6
75°	2.6
77.5°	1.4
80°	1.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)