

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P205372

Luminaire Tested: **LE_6B10D010 EC6B10208050 6LBSLI1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P205372
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B10D010 EC6B10208050 6LBSLI1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH SPECULAR CLEAR TRIM
WATTAGE D010TR-10.05 W DE010-10.58 W D5LT-10.2 W DMX-10.6 W DL2-11.8 W
DL3-11.1 W DLE-11.39 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1484.0 lumens
Efficiency: N/A
Efficacy: 149.9 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 1.04
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 9.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P205372

CATALOG NUMBER: LE_6B10D010 EC6B10208050 6LBSLI1

Luminous Intensity Polar Plot





TEST NUMBER: P205372

CATALOG NUMBER: LE_6B10D010 EC6B10208050 6LBSLI1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20					20					20					20
RC	80				70					50					30					10
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	109	105	102	99	101	99	96	97	95	93	94	92	91	89		
2	103	96	91	86	100	94	89	85	91	87	83	88	84	81	85	82	79	77		
3	95	86	79	74	93	85	78	73	82	76	72	79	75	71	77	73	70	68		
4	88	78	70	64	86	77	69	64	74	68	63	72	67	62	70	65	62	60		
5	82	71	63	57	80	70	62	57	67	61	56	66	60	55	64	59	55	53		
6	76	64	56	51	74	63	56	51	62	55	50	60	54	50	59	53	49	47		
7	71	59	51	46	70	58	51	45	57	50	45	55	49	45	54	49	45	43		
8	67	54	47	41	65	54	46	41	52	46	41	51	45	41	50	45	41	39		
9	63	50	43	38	61	50	43	38	49	42	38	48	42	37	47	41	37	36		
10	59	47	40	35	58	46	39	35	45	39	35	45	39	34	44	38	34	33		

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P205372

CATALOG NUMBER: LE_6B10D010 EC6B10208050 6LBSLI1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	86.3	5.8
10°-20°	219.7	14.8
20°-30°	280.1	18.9
30°-40°	290.5	19.6
40°-50°	267.7	18.0
50°-60°	201.4	13.6
60°-70°	108.7	7.3
70°-80°	29.1	2.0
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	586.1	39.5
0°-40°	876.6	59.1
0°-60°	1345.7	90.7
0°-90°	1484.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1484.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	936	
5°	922	86
15°	784	220
25°	608	280
35°	464	291
45°	348	268
55°	226	201
65°	109	109
75°	25	29
85°	0	0
90°	0	



TEST NUMBER: P205372

CATALOG NUMBER: LE_6B10D010 EC6B10208050 6LBSLI1

CANDELA DISTRIBUTION (FULL):

	0°
0°	936.5
2.5°	933.4
5°	922.2
7.5°	901.8
10°	865.5
12.5°	829.2
15°	783.5
17.5°	741.0
20°	696.9
22.5°	651.1
25°	608.5
27.5°	567.5
30°	529.8
32.5°	495.0
35°	463.5
37.5°	433.5
40°	405.1
42.5°	375.2
45°	348.4
47.5°	318.5
50°	288.5
52.5°	257.0
55°	225.5
57.5°	193.9
60°	164.0
62.5°	135.6
65°	108.8
67.5°	83.5
70°	61.5
72.5°	42.6
75°	25.2
77.5°	11.0
80°	3.1
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)