

Scaled data based on original data using

LM-41-14 Approved Method for Photometric Testing Of Indoor Fluorescent Luminaires

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P204355

Luminaire Tested: **LE_6B15D010 EC6B10208027 6LBSGPH1**

Issue Date: 3/3/2020

Test Information

Test Method: LM-41-14
Report Number: P204355
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P35319)
Test Lab: INNOVATION CENTER-P3
Issue Date: 3/3/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LE_6B15D010 EC6B10208027 6LBSGPH1
Description: PORTFOLIO 6 INCH SHALLOW RECESSED DOWNLIGHT
SHALLOW DISTRIBUTION WITH GRAPHITE HAZE TRIM
WATTAGE D010TR-14.39 W DE010-14.29 W D5LT-14.34 W DMX-14.46 W DL2-15.8 W
DL3-15.28 W DLE-15.432 W
Light Source: HIGH LUMEN LED
Ballast/Driver: ELECTRONIC DRIVER

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1675.5 lumens
Efficiency: N/A
Efficacy: 117.2 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.26
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 14.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P204355

CATALOG NUMBER: LE_6B15D010 EC6B10208027 6LBSGPH1

Luminous Intensity Polar Plot






TEST NUMBER: P204355

CATALOG NUMBER: LE_6B15D010 EC6B10208027 6LBSGPH1

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	111	107	103	100	108	105	102	99	101	98	96		97	95	93		93
2	102	95	89	84	100	93	88	83	90	85	82		87	83	80		84
3	94	85	78	72	92	83	77	71	80	75	70		78	73	69		75
4	87	76	68	62	85	75	67	62	72	66	61		70	65	60		68
5	80	68	60	54	78	67	60	54	65	59	53		63	58	53		62
6	74	62	54	48	73	61	53	48	59	52	47		58	52	47		56
7	69	57	48	43	68	56	48	43	54	47	42		53	47	42		52
8	65	52	44	38	63	51	44	38	50	43	38		49	42	38		48
9	60	48	40	35	59	47	40	35	46	39	35		45	39	34		44
10	57	44	37	32	56	44	36	32	43	36	31		42	36	31		41

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P204355

CATALOG NUMBER: LE_6B15D010 EC6B10208027 6LBSGPH1

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	73.3	4.4
10°-20°	205.7	12.3
20°-30°	300.0	17.9
30°-40°	342.1	20.4
40°-50°	328.1	19.6
50°-60°	251.3	15.0
60°-70°	137.9	8.2
70°-80°	36.6	2.2
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	578.9	34.6
0°-40°	921.0	55.0
0°-60°	1500.4	89.6
0°-90°	1675.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1675.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	778	
5°	772	73
15°	730	206
25°	652	300
35°	547	342
45°	426	328
55°	282	251
65°	139	138
75°	32	37
85°	0	1
90°	0	



TEST NUMBER: P204355

CATALOG NUMBER: LE_6B15D010 EC6B10208027 6LBSGPH1

CANDELA DISTRIBUTION (FULL):

	0°
0°	778.2
2.5°	776.2
5°	772.1
7.5°	766.1
10°	758.1
12.5°	744.0
15°	730.0
17.5°	713.9
20°	695.8
22.5°	673.6
25°	651.5
27.5°	629.4
30°	601.2
32.5°	575.1
35°	547.0
37.5°	518.8
40°	490.6
42.5°	460.5
45°	426.2
47.5°	392.1
50°	355.9
52.5°	317.8
55°	281.5
57.5°	245.4
60°	207.1
62.5°	170.9
65°	138.8
67.5°	106.6
70°	78.4
72.5°	52.2
75°	32.1
77.5°	14.1
80°	4.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0



Report Generated By E9808895 / USPTCWHP6082093





— 0°-180°







(END OF REPORT)