

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245293

Luminaire Tested: **LD8B15D010 ER8B15950 8LBM0WH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P245293
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201704)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B15D010 ER8B15950 8LBM0WH
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
90 CRI 5000 CCT WITH WHEAT TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1421.0 lumens
Efficiency: N/A
Efficacy: 98.7 lumens/watt
Spacing Criteria (0/90/45): 0.83 / 0.83 / 0.83
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 14.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P245293

CATALOG NUMBER: LD8B15D010 ER8B15950 8LBM0WH

Luminous Intensity Polar Plot





TEST NUMBER: P245293

CATALOG NUMBER: LD8B15D010 ER8B15950 8LBM0WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				0
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		0
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		100
1	114	111	109	106	111	109	107	105	105	103	101		101	100	98		94
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		88
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		82
4	98	91	85	81	96	89	84	81	87	83	80		85	82	79		76
5	93	85	79	75	92	84	79	75	82	78	74		81	77	73		71
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		67
7	84	75	69	65	83	75	69	65	73	68	65		72	68	64		63
8	80	71	65	61	79	71	65	61	69	64	61		68	64	61		59
9	77	67	61	58	76	67	61	57	66	61	57		65	60	57		56
10	73	64	58	54	72	63	58	54	62	58	54		62	57	54		52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	55006
5°	56064
10°	53453
15°	47197
20°	40901
25°	34562
30°	25972
35°	17392
40°	9737
45°	3912
50°	1353
55°	376
60°	210
65°	182
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P245293

CATALOG NUMBER: LD8B15D010 ER8B15950 8LBM0WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	169.5	11.9
10°-20°	412.4	29.0
20°-30°	457.6	32.2
30°-40°	289.9	20.4
40°-50°	80.4	5.7
50°-60°	9.2	0.6
60°-70°	1.8	0.1
70°-80°	0.2	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1039.4	73.1
0°-40°	1329.4	93.5
0°-60°	1419.0	99.9
0°-90°	1421.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1421.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1784	
5°	1811	169
15°	1478	412
25°	1016	458
35°	462	290
45°	90	80
55°	7	9
65°	2	2
75°	0	0
85°	0	0
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	



TEST NUMBER: P245293

CATALOG NUMBER: LD8B15D010 ER8B15950 8LBM0WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	1783.8
2.5°	1797.0
5°	1811.2
7.5°	1782.9
10°	1707.1
12.5°	1598.9
15°	1478.4
17.5°	1360.1
20°	1246.4
22.5°	1134.8
25°	1015.8
27.5°	876.6
30°	729.4
32.5°	586.9
35°	462.0
37.5°	349.1
40°	241.9
42.5°	150.5
45°	89.7
47.5°	51.6
50°	28.2
52.5°	13.8
55°	7.0
57.5°	5.3
60°	3.4
62.5°	1.8
65°	2.5
67.5°	1.3
70°	0.0
72.5°	0.4
75°	0.0
77.5°	0.4
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P245293

CATALOG NUMBER: LD8B15D010 ER8B15950 8LBM0WH

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)