

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P979790

Luminaire Tested: PRLX-241-935-LL6-C-U-S-BLAK-X

Issue Date: 4/3/2025

**Test Information**

Test Method: LM-79-2024  
Report Number: P979790  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2502-353-16)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 4/3/2025  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PrentaLux  
Catalog Number: PRLX-241-935-LL6-C-U-S-BLAK-X  
Description: 3D PRINTED LUMINAIRE, INTEGRAL LED LIGHT ENGINE, BLACK 241 SHADE WITH CLEAR LENS  
Light Source: 3500K CCT, 90 CRI LEDS  
Ballast/Driver: -

**Summary**


Lumens per Lamp: N/A  
Luminaire Lumens: 2369.1 lumens  
Efficiency: N/A  
Efficacy: 70.7 lumens/watt  
Spacing Criteria (0/90/45): 1.13 / 1.13 / 1.05  
Luminous Opening: Circular (Dia: 1.33' x H: 0')  
CIE Type: Direct

Input Watts (W): 33.5  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT



TEST NUMBER: P979790  
CATALOG NUMBER: PRLX-241-935-LL6-C-U-S-BLAK-X

### Luminous Intensity Polar Plot





TEST NUMBER: P979790

CATALOG NUMBER: PRLX-241-935-LL6-C-U-S-BLAK-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	108	106	111	108	106	104	104	102	101	101	99	98	97	96	95	93
2	108	103	98	95	105	101	97	94	98	94	92	95	92	90	92	90	88	86
3	102	95	90	86	100	94	89	85	91	87	84	89	86	83	87	84	82	80
4	97	89	83	79	95	88	82	78	85	81	77	83	80	76	82	78	76	74
5	91	83	77	72	90	82	76	72	80	75	71	78	74	71	77	73	70	69
6	87	77	71	67	85	77	71	67	75	70	66	74	69	66	72	68	65	64
7	82	72	66	62	81	72	66	62	70	65	61	69	65	61	68	64	61	59
8	78	68	62	57	76	67	61	57	66	61	57	65	60	57	64	60	57	55
9	74	64	58	54	73	63	57	53	62	57	53	61	57	53	61	56	53	51
10	70	60	54	50	69	60	54	50	59	53	50	58	53	50	57	53	49	48

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	17180
5°	16382
10°	15602
15°	15248
20°	15148
25°	15042
30°	14885
35°	13996
40°	2154
45°	350
50°	166
55°	164
60°	188
65°	195
70°	171
75°	182
80°	138
85°	133

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 350 cd/sqm

TEST NUMBER: P979790

CATALOG NUMBER: PRLX-241-935-LL6-C-U-S-BLAK-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	198.1	8.4
10°-20°	540.6	22.8
20°-30°	814.6	34.4
30°-40°	743.0	31.4
40°-50°	43.7	1.8
50°-60°	11.1	0.5
60°-70°	10.0	0.4
70°-80°	5.8	0.2
80°-90°	2.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1553.4	65.6
0°-40°	2296.4	96.9
0°-60°	2351.2	99.2
0°-90°	2369.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2369.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	2228	
5°	2117	198
15°	1910	541
25°	1768	815
35°	1487	743
45°	32	44
55°	12	11
65°	11	10
75°	6	6
85°	2	2
90°	0	



TEST NUMBER: P979790

CATALOG NUMBER: PRLX-241-935-LL6-C-U-S-BLAK-X

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	2228.5
2.5°	2199.4
5°	2116.9
7.5°	2042.0
10°	1993.1
12.5°	1948.8
15°	1910.5
17.5°	1878.4
20°	1846.4
22.5°	1815.8
25°	1768.4
27.5°	1718.0
30°	1672.1
32.5°	1618.6
35°	1487.2
37.5°	800.9
40°	214.0
42.5°	71.8
45°	32.1
47.5°	16.8
50°	13.8
52.5°	12.2
55°	12.2
57.5°	12.2
60°	12.2
62.5°	10.7
65°	10.7
67.5°	9.2
70°	7.6
72.5°	6.1
75°	6.1
77.5°	4.6
80°	3.1
82.5°	3.1
85°	1.5
87.5°	1.5
90°	0.0



TEST NUMBER: P979790  
 CATALOG NUMBER: PRLX-241-935-LL6-C-U-S-BLAK-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.05
	12H	0.00	0.00	0.00	0.00	0.17	0.00	0.00	0.00	0.00	0.17
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.25	0.00	0.00	0.00	0.00	0.25
	6H	0.00	0.00	0.00	0.34	0.81	0.00	0.00	0.00	0.34	0.81
	8H	0.00	0.14	0.19	0.59	1.07	0.00	0.14	0.19	0.59	1.07
	12H	0.00	0.26	0.38	0.75	1.23	0.00	0.26	0.38	0.75	1.23
8H	4H	0.00	0.00	0.00	0.00	0.44	0.00	0.00	0.00	0.00	0.44
	6H	0.00	0.14	0.32	0.65	1.14	0.00	0.14	0.32	0.65	1.14
	8H	0.22	0.51	0.75	1.04	1.54	0.22	0.51	0.75	1.04	1.54
	12H	0.49	0.75	1.02	1.25	1.83	0.49	0.75	1.02	1.25	1.83
12H	4H	0.00	0.00	0.00	0.00	0.42	0.00	0.00	0.00	0.00	0.42
	6H	0.00	0.16	0.39	0.68	1.18	0.00	0.16	0.39	0.68	1.18
	8H	0.34	0.60	0.86	1.10	1.68	0.34	0.60	0.86	1.10	1.68