

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1244810

Luminaire Tested: PRLX-MIN-L-930-05L-U-NL

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1244810
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2412-299-9)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-MIN-L-930-05L-U-NL
Description: 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, NATURAL LINES SHADE TEXTURE
LIGHT LEVEL 2
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 501.1 lumens
Efficiency: N/A
Efficacy: 33.9 lumens/watt
Spacing Criteria (0/90/45): 0.2 / 0.2 / 0.18
Luminous Opening: Rectangular w/ Sides (W: 0.58' x L: 0.58' x H: 1.92')
CIE Type: General Diffuse

Input Watts (W): 14.8
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

Luminous Intensity Polar Plot





TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	62	62	62	56		
1	95	89	83	78	88	82	77	73	70	66	63	59	56	53	48	46	44	39		
2	85	76	68	62	79	70	63	58	60	54	50	50	46	42	41	38	35	30		
3	77	66	57	50	71	61	53	47	52	46	41	43	39	35	36	32	29	25		
4	71	58	49	42	65	54	46	40	46	40	35	39	34	30	32	28	25	21		
5	65	52	43	36	60	48	40	34	41	35	30	35	30	26	29	25	22	18		
6	60	47	38	32	55	44	36	30	38	31	26	32	27	23	27	22	19	16		
7	56	43	34	28	52	40	32	27	35	28	24	29	24	21	25	21	18	15		
8	52	39	31	25	48	37	29	24	32	26	21	27	22	19	23	19	16	14		
9	49	36	28	23	45	34	27	22	30	24	20	26	21	17	22	18	15	13		
10	46	34	26	21	43	32	25	20	28	22	18	24	19	16	21	17	14	12		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	22974
5°	10535
10°	2455
15°	937
20°	606
25°	482
30°	429
35°	400
40°	387
45°	381
50°	377
55°	380
60°	383
65°	389
70°	392
75°	396
80°	397
85°	405

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 90°

Luminance: 414 cd/sqm

TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.6	6.1
10°-20°	16.9	3.4
20°-30°	16.4	3.3
30°-40°	21.6	4.3
40°-50°	28.3	5.6
50°-60°	35.2	7.0
60°-70°	41.4	8.3
70°-80°	45.3	9.0
80°-90°	46.8	9.3
90°-100°	46.9	9.4
100°-110°	44.6	8.9
110°-120°	39.4	7.9
120°-130°	32.5	6.5
130°-140°	24.5	4.9
140°-150°	16.6	3.3
150°-160°	9.7	1.9
160°-170°	4.0	0.8
170°-180°	0.4	0.1
0°-30°	63.9	12.8
0°-40°	85.5	17.1
0°-60°	149.0	29.7
0°-90°	282.5	56.4
90°-120°	130.9	26.1
90°-150°	204.5	40.8
90°-180°	219.0	43.7
0°-180°	501.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	726	
5°	427	31
15°	54	17
25°	35	16
35°	34	22
45°	36	28
55°	39	35
65°	42	41
75°	43	45
85°	43	35
90°	43	24
95°	43	35
105°	42	45
115°	40	39
125°	36	32
135°	32	25
145°	26	17
155°	21	10
165°	14	4
175°	2	0
180°	0	

TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

CANDELA DISTRIBUTION (FULL):

0°	
0°	726.2
2.5°	796.6
5°	427.1
7.5°	173.8
10°	120.7
12.5°	74.0
15°	53.8
17.5°	44.8
20°	39.5
22.5°	36.7
25°	35.0
27.5°	34.2
30°	34.0
32.5°	34.0
35°	34.2
37.5°	34.5
40°	35.2
42.5°	35.7
45°	36.5
47.5°	37.2
50°	37.7
52.5°	38.5
55°	39.2
57.5°	40.0
60°	40.5
62.5°	41.3
65°	41.8
67.5°	42.3
70°	42.5
72.5°	42.8
75°	43.0
77.5°	42.8
80°	42.8
82.5°	42.8
85°	43.0
87.5°	43.0
90°	43.0
92.5°	43.0
95°	43.0
97.5°	43.0
100°	42.8
102.5°	42.5
105°	42.3
107.5°	41.8
110°	41.3

TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

CANDELA DISTRIBUTION (continued):

	0°
112.5°	40.5
115°	39.7
117.5°	39.0
120°	38.0
122.5°	37.2
125°	36.2
127.5°	35.2
130°	34.0
132.5°	33.0
135°	31.7
137.5°	30.2
140°	28.9
142.5°	27.7
145°	26.2
147.5°	24.9
150°	23.6
152.5°	22.1
155°	20.9
157.5°	19.4
160°	17.9
162.5°	16.1
165°	14.1
167.5°	11.3
170°	7.8
172.5°	4.8
175°	2.0
177.5°	0.5
180°	0.3

TEST NUMBER: P1244810

CATALOG NUMBER: PRLX-MIN-L-930-05L-U-NL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	4.3	5.3	5.1	6.2	7.4	4.3	5.3	5.1	6.2	7.4
	3H	7.3	8.2	8.2	9.1	10.3	7.3	8.2	8.2	9.1	10.3
	4H	8.7	9.6	9.6	10.5	11.7	8.7	9.6	9.6	10.5	11.7
	6H	10.1	11.0	11.0	11.9	13.1	10.1	11.0	11.0	11.9	13.1
	8H	10.8	11.6	11.7	12.5	13.7	10.8	11.6	11.7	12.5	13.7
	12H	11.4	12.2	12.3	13.2	14.4	11.4	12.2	12.3	13.2	14.4
4H	2H	5.0	6.0	5.9	6.9	8.1	5.0	6.0	5.9	6.9	8.1
	3H	8.2	9.0	9.1	10.0	11.2	8.2	9.0	9.1	10.0	11.2
	4H	9.8	10.5	10.7	11.5	12.7	9.8	10.5	10.7	11.5	12.7
	6H	11.4	12.0	12.3	13.0	14.2	11.4	12.0	12.3	13.0	14.2
	8H	12.1	12.7	13.1	13.7	15.0	12.1	12.7	13.1	13.7	15.0
	12H	12.9	13.5	13.8	14.4	15.7	12.9	13.5	13.8	14.4	15.7
8H	4H	10.3	10.9	11.2	11.9	13.2	10.3	10.9	11.2	11.9	13.2
	6H	12.1	12.6	13.0	13.6	14.9	12.1	12.6	13.0	13.6	14.9
	8H	13.0	13.5	13.9	14.5	15.7	13.0	13.5	13.9	14.5	15.7
	12H	13.9	14.3	14.9	15.3	16.6	13.9	14.3	14.9	15.3	16.6
12H	4H	10.4	11.0	11.4	12.0	13.2	10.4	11.0	11.4	12.0	13.2
	6H	12.3	12.7	13.2	13.7	15.0	12.3	12.7	13.2	13.7	15.0
	8H	13.2	13.7	14.2	14.7	16.0	13.2	13.7	14.2	14.7	16.0

(END OF REPORT)