

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1244911

Luminaire Tested: PRLX-MIN-M-935-01L-U-PS

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1244911
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2412-299-23)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-MIN-M-935-01L-U-PS
Description: 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, PINSTRIPE SHADE TEXTURE
LIGHT LEVEL 1
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 159.5 lumens
Efficiency: N/A
Efficacy: 25.3 lumens/watt
Spacing Criteria (0/90/45): 0.21 / 0.21 / 0.18
Luminous Opening: Rectangular w/ Sides (W: 0.46' x L: 0.46' x H: 1.92')
CIE Type: General Diffuse

Input Watts (W): 6.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

Luminous Intensity Polar Plot



TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20						20
RC	80					70					50					30						10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10	
RCR																						
0	109	109	109	109		101	101	101	101		87	87	87		74	74	74		62	62	62	
1	95	89	84	79		88	82	78	73		70	66	63		59	56	53		48	46	44	
2	86	76	69	62		79	71	64	58		60	55	50		50	46	42		41	38	35	
3	78	67	58	51		71	62	54	48		52	46	41		44	39	35		36	32	29	
4	71	59	50	43		65	55	47	41		47	40	35		39	34	30		32	28	25	
5	66	53	44	37		60	49	41	35		42	36	31		36	31	27		29	26	22	
6	61	48	39	33		56	45	37	31		38	32	27		33	28	24		27	23	20	
7	57	44	35	29		52	41	33	28		35	29	25		30	25	22		25	21	19	
8	53	40	32	27		49	38	30	25		33	27	22		28	23	20		24	20	17	
9	50	37	29	24		46	35	28	23		31	25	21		26	22	18		23	19	16	
10	47	35	27	22		44	33	26	21		29	23	19		25	20	17		21	18	15	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13934
5°	7043
10°	1261
15°	403
20°	251
25°	203
30°	177
35°	162
40°	157
45°	154
50°	152
55°	151
60°	152
65°	153
70°	156
75°	160
80°	162
85°	166

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
Vertical Angle: 90°
Luminance: 169 cd/sqm

TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	12.0	7.5
10°-20°	5.2	3.3
20°-30°	4.9	3.1
30°-40°	6.5	4.1
40°-50°	8.5	5.3
50°-60°	10.6	6.6
60°-70°	12.5	7.8
70°-80°	14.2	8.9
80°-90°	15.0	9.4
90°-100°	15.0	9.4
100°-110°	14.2	8.9
110°-120°	12.7	8.0
120°-130°	10.5	6.6
130°-140°	7.9	5.0
140°-150°	5.4	3.4
150°-160°	3.0	1.9
160°-170°	1.2	0.8
170°-180°	0.1	0.1
0°-30°	22.1	13.9
0°-40°	28.6	17.9
0°-60°	47.7	29.9
0°-90°	89.4	56.1
90°-120°	41.9	26.3
90°-150°	65.7	41.2
90°-180°	70.0	43.9
0°-180°	159.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	272	
5°	187	12
15°	16	5
25°	11	5
35°	10	6
45°	11	9
55°	12	11
65°	13	13
75°	13	14
85°	14	11
90°	14	8
95°	14	11
105°	13	14
115°	13	13
125°	12	10
135°	10	8
145°	9	5
155°	7	3
165°	4	1
175°	0	0
180°	0	

TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

CANDELA DISTRIBUTION (FULL):

0°	
0°	271.9
2.5°	300.4
5°	187.0
7.5°	62.0
10°	42.1
12.5°	23.1
15°	16.1
17.5°	13.2
20°	11.6
22.5°	11.0
25°	10.6
27.5°	10.2
30°	10.2
32.5°	10.2
35°	10.2
37.5°	10.4
40°	10.6
42.5°	10.8
45°	11.0
47.5°	11.2
50°	11.4
52.5°	11.6
55°	11.8
57.5°	12.0
60°	12.2
62.5°	12.4
65°	12.6
67.5°	12.8
70°	13.0
72.5°	13.2
75°	13.4
77.5°	13.6
80°	13.6
82.5°	13.8
85°	13.8
87.5°	13.8
90°	13.8
92.5°	13.8
95°	13.8
97.5°	13.8
100°	13.6
102.5°	13.6
105°	13.4
107.5°	13.4
110°	13.2

TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

CANDELA DISTRIBUTION (continued):

	0°
112.5°	13.0
115°	12.8
117.5°	12.6
120°	12.2
122.5°	12.0
125°	11.6
127.5°	11.4
130°	11.0
132.5°	10.6
135°	10.2
137.5°	9.8
140°	9.4
142.5°	9.0
145°	8.6
147.5°	8.2
150°	7.6
152.5°	7.0
155°	6.6
157.5°	6.0
160°	5.4
162.5°	5.0
165°	4.2
167.5°	3.4
170°	2.4
172.5°	1.4
175°	0.4
177.5°	0.0
180°	0.0

TEST NUMBER: P1244911

CATALOG NUMBER: PRLX-MIN-M-935-01L-U-PS

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.8	1.8	1.7	2.8	3.9	0.8	1.8	1.7	2.8	3.9
	3H	3.9	4.8	4.7	5.7	6.9	3.9	4.8	4.7	5.7	6.9
	4H	5.3	6.2	6.2	7.2	8.4	5.3	6.2	6.2	7.2	8.4
	6H	6.8	7.7	7.7	8.6	9.8	6.8	7.7	7.7	8.6	9.8
	8H	7.5	8.3	8.5	9.3	10.5	7.5	8.3	8.5	9.3	10.5
	12H	8.2	9.0	9.2	10.0	11.2	8.2	9.0	9.2	10.0	11.2
4H	2H	1.6	2.5	2.5	3.4	4.6	1.6	2.5	2.5	3.4	4.6
	3H	4.8	5.6	5.7	6.6	7.8	4.8	5.6	5.7	6.6	7.8
	4H	6.5	7.2	7.4	8.1	9.4	6.5	7.2	7.4	8.1	9.4
	6H	8.1	8.8	9.0	9.7	11.0	8.1	8.8	9.0	9.7	11.0
	8H	8.9	9.5	9.8	10.5	11.8	8.9	9.5	9.8	10.5	11.8
	12H	9.7	10.3	10.7	11.3	12.5	9.7	10.3	10.7	11.3	12.5
8H	4H	7.0	7.6	7.9	8.6	9.8	7.0	7.6	7.9	8.6	9.8
	6H	8.8	9.4	9.8	10.4	11.6	8.8	9.4	9.8	10.4	11.6
	8H	9.8	10.3	10.8	11.3	12.5	9.8	10.3	10.8	11.3	12.5
	12H	10.8	11.2	11.7	12.2	13.5	10.8	11.2	11.7	12.2	13.5
12H	4H	7.1	7.7	8.1	8.7	9.9	7.1	7.7	8.1	8.7	9.9
	6H	9.0	9.5	10.0	10.5	11.8	9.0	9.5	10.0	10.5	11.8
	8H	10.1	10.5	11.0	11.5	12.8	10.1	10.5	11.0	11.5	12.8

(END OF REPORT)