

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1244912

Luminaire Tested: PRLX-MIN-M-935-03L-U-NL

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1244912
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2412-299-23)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-MIN-M-935-03L-U-NL
Description: 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, NATURAL LINES SHADE TEXT LIGHT LEVEL 2
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 295.0 lumens
Efficiency: N/A
Efficacy: 26.6 lumens/watt
Spacing Criteria (0/90/45): 0.21 / 0.21 / 0.18
Luminous Opening: Rectangular w/ Sides (W: 0.46' x L: 0.46' x H: 1.92')
CIE Type: General Diffuse

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

Luminous Intensity Polar Plot





TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	62	62	62	56		
1	95	89	84	79	88	82	78	73	70	66	63	59	56	53	48	46	44	39		
2	86	76	69	62	79	71	64	58	60	55	50	50	46	42	41	38	35	31		
3	78	67	58	51	71	62	54	48	52	46	41	44	39	35	36	32	29	25		
4	71	59	50	43	65	55	47	41	47	40	35	39	34	30	32	28	25	22		
5	66	53	44	37	60	49	41	35	42	36	31	36	31	27	29	26	22	19		
6	61	48	39	33	56	45	37	31	38	32	27	33	28	24	27	23	20	17		
7	57	44	35	29	52	41	33	28	35	29	25	30	25	22	25	21	19	16		
8	53	40	32	27	49	38	30	25	33	27	22	28	23	20	24	20	17	15		
9	50	37	29	24	46	35	28	23	31	25	21	26	22	18	23	19	16	14		
10	47	35	27	22	44	33	26	21	29	23	19	25	20	17	21	18	15	13		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	25690
5°	12986
10°	2327
15°	741
20°	465
25°	376
30°	328
35°	301
40°	291
45°	284
50°	281
55°	279
60°	281
65°	283
70°	288
75°	296
80°	301
85°	307

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 90°

Luminance: 312 cd/sqm

TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	22.1	7.5
10°-20°	9.7	3.3
20°-30°	9.1	3.1
30°-40°	12.0	4.1
40°-50°	15.8	5.3
50°-60°	19.6	6.6
60°-70°	23.1	7.8
70°-80°	26.2	8.9
80°-90°	27.8	9.4
90°-100°	27.8	9.4
100°-110°	26.3	8.9
110°-120°	23.5	8.0
120°-130°	19.4	6.6
130°-140°	14.6	5.0
140°-150°	10.0	3.4
150°-160°	5.6	1.9
160°-170°	2.2	0.8
170°-180°	0.2	0.1
0°-30°	40.8	13.8
0°-40°	52.8	17.9
0°-60°	88.2	29.9
0°-90°	165.3	56.0
90°-120°	77.6	26.3
90°-150°	121.6	41.2
90°-180°	130.0	44.1
0°-180°	295.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	501	
5°	345	22
15°	30	10
25°	20	9
35°	19	12
45°	20	16
55°	22	20
65°	23	23
75°	25	26
85°	26	21
90°	26	14
95°	26	21
105°	25	26
115°	24	23
125°	22	19
135°	19	15
145°	16	10
155°	12	6
165°	8	2
175°	1	0
180°	0	

TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

CANDELA DISTRIBUTION (FULL):

0°	
0°	501.3
2.5°	553.9
5°	344.8
7.5°	114.3
10°	77.7
12.5°	42.5
15°	29.6
17.5°	24.4
20°	21.5
22.5°	20.3
25°	19.6
27.5°	18.9
30°	18.9
32.5°	18.9
35°	18.9
37.5°	19.2
40°	19.6
42.5°	20.0
45°	20.3
47.5°	20.7
50°	21.1
52.5°	21.5
55°	21.8
57.5°	22.2
60°	22.6
62.5°	22.9
65°	23.3
67.5°	23.7
70°	24.0
72.5°	24.4
75°	24.8
77.5°	25.2
80°	25.2
82.5°	25.5
85°	25.5
87.5°	25.5
90°	25.5
92.5°	25.5
95°	25.5
97.5°	25.5
100°	25.2
102.5°	25.2
105°	24.8
107.5°	24.8
110°	24.4

TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

CANDELA DISTRIBUTION (continued):

	0°
112.5°	24.0
115°	23.7
117.5°	23.3
120°	22.6
122.5°	22.2
125°	21.5
127.5°	21.1
130°	20.3
132.5°	19.6
135°	18.9
137.5°	18.1
140°	17.4
142.5°	16.6
145°	15.9
147.5°	15.2
150°	14.1
152.5°	12.9
155°	12.2
157.5°	11.1
160°	10.0
162.5°	9.2
165°	7.8
167.5°	6.3
170°	4.4
172.5°	2.6
175°	0.7
177.5°	0.0
180°	0.0

TEST NUMBER: P1244912

CATALOG NUMBER: PRLX-MIN-M-935-03L-U-NL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	3.0	4.0	3.8	4.9	6.1	3.0	4.0	3.8	4.9	6.1
	3H	6.0	6.9	6.9	7.9	9.1	6.0	6.9	6.9	7.9	9.1
	4H	7.5	8.4	8.4	9.3	10.5	7.5	8.4	8.4	9.3	10.5
	6H	9.0	9.8	9.9	10.8	12.0	9.0	9.8	9.9	10.8	12.0
	8H	9.7	10.5	10.6	11.4	12.7	9.7	10.5	10.6	11.4	12.7
	12H	10.4	11.1	11.3	12.1	13.3	10.4	11.1	11.3	12.1	13.3
4H	2H	3.7	4.6	4.6	5.6	6.8	3.7	4.6	4.6	5.6	6.8
	3H	6.9	7.7	7.9	8.7	9.9	6.9	7.7	7.9	8.7	9.9
	4H	8.6	9.3	9.5	10.3	11.5	8.6	9.3	9.5	10.3	11.5
	6H	10.2	10.9	11.2	11.9	13.1	10.2	10.9	11.2	11.9	13.1
	8H	11.0	11.7	12.0	12.6	13.9	11.0	11.7	12.0	12.6	13.9
	12H	11.8	12.4	12.8	13.4	14.7	11.8	12.4	12.8	13.4	14.7
8H	4H	9.1	9.7	10.1	10.7	12.0	9.1	9.7	10.1	10.7	12.0
	6H	11.0	11.5	11.9	12.5	13.8	11.0	11.5	11.9	12.5	13.8
	8H	11.9	12.4	12.9	13.4	14.7	11.9	12.4	12.9	13.4	14.7
	12H	12.9	13.3	13.9	14.3	15.6	12.9	13.3	13.9	14.3	15.6
12H	4H	9.2	9.8	10.2	10.8	12.1	9.2	9.8	10.2	10.8	12.1
	6H	11.2	11.7	12.1	12.6	13.9	11.2	11.7	12.1	12.6	13.9
	8H	12.2	12.6	13.2	13.6	14.9	12.2	12.6	13.2	13.6	14.9

(END OF REPORT)