

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1245132

Luminaire Tested: PRLX-NIM-M-927-03L-U-NL

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1245132  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2412-299-15)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PrentaLux  
Catalog Number: PRLX-NIM-M-927-03L-U-NL  
Description: 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, NATURAL LINES SHADE TEXT LIGHT LEVEL 2  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 267.9 lumens  
Efficiency: N/A  
Efficacy: 24.1 lumens/watt  
Spacing Criteria (0/90/45): 0.2 / 0.2 / 0.18  
Luminous Opening: Rectangular w/ Sides (W: 0.46' x L: 0.46' x H: 1.92')  
CIE Type: General Diffuse  
  
Input Watts (W): 11.1  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 28.75 FT

TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

### Luminous Intensity Polar Plot





TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	108	108	108	108	101	101	101	101	86	86	86		73	73	73		61	61	61	56
1	95	89	83	78	88	82	77	73	70	66	63		58	55	53		48	46	44	38
2	85	76	68	62	78	70	63	58	60	54	50		50	46	42		40	37	35	30
3	77	66	58	51	71	61	54	47	52	46	41		43	39	35		35	32	29	25
4	71	59	50	43	65	54	46	40	46	40	35		39	34	30		32	28	25	21
5	65	52	43	37	60	49	41	35	42	35	30		35	30	26		29	25	22	18
6	60	47	39	32	56	44	36	30	38	32	27		32	27	23		27	23	20	17
7	56	43	35	29	52	40	33	27	35	29	24		30	25	21		25	21	18	15
8	53	40	32	26	49	37	30	25	32	26	22		28	23	19		23	19	17	14
9	49	37	29	24	46	34	27	22	30	24	20		26	21	18		22	18	15	13
10	47	34	27	22	43	32	25	21	28	22	19		24	20	17		21	17	15	13

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	24137
5°	10583
10°	2043
15°	673
20°	402
25°	316
30°	286
35°	263
40°	276
45°	260
50°	248
55°	265
60°	257
65°	276
70°	272
75°	271
80°	271
85°	273

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 90°  
 Luminance: 278 cd/sqm

TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	18.7	7.0
10°-20°	8.6	3.2
20°-30°	7.7	2.9
30°-40°	10.5	3.9
40°-50°	14.4	5.4
50°-60°	18.3	6.8
60°-70°	21.8	8.1
70°-80°	24.0	9.0
80°-90°	24.8	9.2
90°-100°	24.8	9.2
100°-110°	24.0	9.0
110°-120°	22.3	8.3
120°-130°	18.3	6.8
130°-140°	13.8	5.2
140°-150°	8.8	3.3
150°-160°	5.1	1.9
160°-170°	1.7	0.6
170°-180°	0.2	0.1
0°-30°	35.1	13.1
0°-40°	45.6	17.0
0°-60°	78.4	29.3
0°-90°	149.0	55.6
90°-120°	71.1	26.5
90°-150°	112.1	41.8
90°-180°	119.0	44.4
0°-180°	267.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	471	
5°	281	19
15°	27	9
25°	16	8
35°	16	11
45°	19	14
55°	21	18
65°	23	22
75°	23	24
85°	23	19
90°	23	12
95°	23	19
105°	23	24
115°	23	22
125°	21	18
135°	19	14
145°	14	9
155°	10	5
165°	6	2
175°	0	0
180°	0	

TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	471.0
2.5°	473.1
5°	281.0
7.5°	99.2
10°	68.2
12.5°	39.3
15°	26.9
17.5°	20.7
20°	18.6
22.5°	16.5
25°	16.5
27.5°	16.5
30°	16.5
32.5°	16.5
35°	16.5
37.5°	16.5
40°	18.6
42.5°	18.6
45°	18.6
47.5°	18.6
50°	18.6
52.5°	20.7
55°	20.7
57.5°	20.7
60°	20.7
62.5°	20.7
65°	22.7
67.5°	22.7
70°	22.7
72.5°	22.7
75°	22.7
77.5°	22.7
80°	22.7
82.5°	22.7
85°	22.7
87.5°	22.7
90°	22.7
92.5°	22.7
95°	22.7
97.5°	22.7
100°	22.7
102.5°	22.7
105°	22.7
107.5°	22.7
110°	22.7

TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	22.7
115°	22.7
117.5°	22.7
120°	20.7
122.5°	20.7
125°	20.7
127.5°	20.7
130°	18.6
132.5°	18.6
135°	18.6
137.5°	16.5
140°	16.5
142.5°	14.5
145°	14.5
147.5°	12.4
150°	12.4
152.5°	12.4
155°	10.3
157.5°	10.3
160°	8.3
162.5°	6.2
165°	6.2
167.5°	4.1
170°	4.1
172.5°	2.1
175°	0.0
177.5°	0.0
180°	0.0



TEST NUMBER: P1245132

CATALOG NUMBER: PRLX-NIM-M-927-03L-U-NL

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	2.8	3.8	3.7	4.7	5.9	2.8	3.8	3.7	4.7	5.9
	3H	5.9	6.9	6.8	7.8	9.0	5.9	6.9	6.8	7.8	9.0
	4H	7.3	8.2	8.2	9.2	10.4	7.3	8.2	8.2	9.2	10.4
	6H	8.7	9.6	9.7	10.5	11.7	8.7	9.6	9.7	10.5	11.7
	8H	9.4	10.2	10.3	11.2	12.4	9.4	10.2	10.3	11.2	12.4
	12H	10.0	10.8	11.0	11.8	13.0	10.0	10.8	11.0	11.8	13.0
4H	2H	3.6	4.5	4.5	5.5	6.7	3.6	4.5	4.5	5.5	6.7
	3H	6.9	7.7	7.8	8.6	9.9	6.9	7.7	7.8	8.6	9.9
	4H	8.4	9.2	9.4	10.1	11.4	8.4	9.2	9.4	10.1	11.4
	6H	10.0	10.6	10.9	11.6	12.9	10.0	10.6	10.9	11.6	12.9
	8H	10.8	11.4	11.7	12.3	13.6	10.8	11.4	11.7	12.3	13.6
	12H	11.5	12.1	12.5	13.1	14.3	11.5	12.1	12.5	13.1	14.3
8H	4H	8.9	9.6	9.9	10.5	11.8	8.9	9.6	9.9	10.5	11.8
	6H	10.7	11.2	11.7	12.2	13.5	10.7	11.2	11.7	12.2	13.5
	8H	11.6	12.1	12.6	13.1	14.4	11.6	12.1	12.6	13.1	14.4
	12H	12.5	13.0	13.5	14.0	15.3	12.5	13.0	13.5	14.0	15.3
12H	4H	9.1	9.6	10.0	10.6	11.9	9.1	9.6	10.0	10.6	11.9
	6H	10.9	11.4	11.9	12.4	13.7	10.9	11.4	11.9	12.4	13.7
	8H	11.9	12.3	12.8	13.3	14.6	11.9	12.3	12.8	13.3	14.6

(END OF REPORT)