

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1245213

Luminaire Tested: PRLX-NIM-S-927-05L-U-NR

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1245213
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2412-299-2)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-NIM-S-927-05L-U-NR
Description: 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, NATURAL RIBS SHADE TEXTURED
LIGHT LEVEL 2
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 489.1 lumens
Efficiency: N/A
Efficacy: 44.1 lumens/watt
Spacing Criteria (0/90/45): 0.43 / 0.43 / 0.4
Luminous Opening: Rectangular w/ Sides (W: 0.58' x L: 0.58' x H: 0.87')
CIE Type: Semi-Direct

Input Watts (W): 11.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

Luminous Intensity Polar Plot





TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	113	113	113	113	107	107	107	107	96	96	96	87	87	87	78	78	78	74		
1	101	96	91	87	96	91	87	83	82	79	76	74	71	69	66	64	62	58		
2	92	84	77	71	87	80	73	68	72	67	63	65	61	57	58	55	52	49		
3	85	74	66	60	80	71	64	58	64	58	53	58	53	49	52	48	45	42		
4	78	67	58	52	74	64	56	50	58	52	47	52	47	43	47	43	40	37		
5	72	60	52	46	69	58	50	44	53	46	41	48	43	39	44	39	36	33		
6	68	55	47	41	64	53	45	40	48	42	37	44	39	35	41	36	33	30		
7	63	51	43	37	60	49	41	36	45	39	34	41	36	32	38	33	30	28		
8	59	47	39	34	56	45	38	33	42	36	31	39	33	30	36	31	28	26		
9	56	44	36	31	53	42	35	30	39	33	29	36	31	27	34	29	26	24		
10	53	41	34	29	51	40	33	28	37	31	27	34	29	26	32	28	24	23		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13028
5°	12855
10°	11304
15°	2745
20°	2289
25°	1907
30°	1506
35°	1249
40°	1068
45°	966
50°	875
55°	809
60°	763
65°	708
70°	671
75°	640
80°	578
85°	549

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 966 cd/sqm

TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	42.7	8.7
10°-20°	45.3	9.3
20°-30°	42.2	8.6
30°-40°	41.5	8.5
40°-50°	41.4	8.5
50°-60°	41.2	8.4
60°-70°	39.7	8.1
70°-80°	36.1	7.4
80°-90°	30.1	6.1
90°-100°	28.8	5.9
100°-110°	27.0	5.5
110°-120°	23.6	4.8
120°-130°	19.3	3.9
130°-140°	14.4	2.9
140°-150°	9.3	1.9
150°-160°	4.8	1.0
160°-170°	1.7	0.3
170°-180°	0.2	0.0
0°-30°	130.1	26.6
0°-40°	171.6	35.1
0°-60°	254.2	52.0
0°-90°	360.1	73.6
90°-120°	79.4	16.2
90°-150°	122.3	25.0
90°-180°	129.0	26.4
0°-180°	489.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	412	
5°	458	43
15°	117	45
25°	93	42
35°	66	42
45°	54	41
55°	46	41
65°	40	40
75°	34	36
85°	27	23
90°	26	15
95°	26	22
105°	26	27
115°	24	24
125°	21	19
135°	18	14
145°	15	9
155°	11	5
165°	5	2
175°	1	0
180°	0	

TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

CANDELA DISTRIBUTION (FULL):

0°	
0°	411.8
2.5°	425.0
5°	457.6
7.5°	452.4
10°	444.4
12.5°	190.5
15°	117.3
17.5°	111.1
20°	104.9
22.5°	99.6
25°	92.6
27.5°	84.7
30°	76.7
32.5°	70.5
35°	66.1
37.5°	61.7
40°	58.2
42.5°	55.6
45°	53.8
47.5°	51.1
50°	49.4
52.5°	47.6
55°	45.9
57.5°	44.1
60°	43.2
62.5°	41.4
65°	39.7
67.5°	38.8
70°	37.0
72.5°	36.2
75°	34.4
77.5°	32.6
80°	30.0
82.5°	28.2
85°	27.3
87.5°	26.5
90°	26.5
92.5°	26.5
95°	26.5
97.5°	26.5
100°	25.6
102.5°	25.6
105°	25.6
107.5°	25.6
110°	24.7

TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

CANDELA DISTRIBUTION (continued):

	0°
112.5°	24.7
115°	23.8
117.5°	22.9
120°	22.9
122.5°	22.0
125°	21.2
127.5°	21.2
130°	20.3
132.5°	19.4
135°	18.5
137.5°	17.6
140°	16.8
142.5°	15.9
145°	15.0
147.5°	13.2
150°	12.3
152.5°	11.5
155°	10.6
157.5°	8.8
160°	7.9
162.5°	7.1
165°	5.3
167.5°	4.4
170°	3.5
172.5°	1.8
175°	0.9
177.5°	0.0
180°	0.0

TEST NUMBER: P1245213

CATALOG NUMBER: PRLX-NIM-S-927-05L-U-NR

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	7.8	8.9	8.5	9.7	10.6	7.8	8.9	8.5	9.7	10.6
	3H	10.1	11.2	10.8	11.9	12.8	10.1	11.2	10.8	11.9	12.8
	4H	11.2	12.2	11.9	12.9	13.9	11.2	12.2	11.9	12.9	13.9
	6H	12.2	13.1	12.9	13.9	14.8	12.2	13.1	12.9	13.9	14.8
	8H	12.6	13.5	13.4	14.3	15.2	12.6	13.5	13.4	14.3	15.2
	12H	13.0	13.8	13.8	14.6	15.6	13.0	13.8	13.8	14.6	15.6
4H	2H	8.4	9.4	9.2	10.2	11.1	8.4	9.4	9.2	10.2	11.1
	3H	10.9	11.8	11.7	12.6	13.5	10.9	11.8	11.7	12.6	13.5
	4H	12.1	12.9	12.9	13.7	14.7	12.1	12.9	12.9	13.7	14.7
	6H	13.3	14.0	14.1	14.8	15.8	13.3	14.0	14.1	14.8	15.8
	8H	13.8	14.4	14.6	15.3	16.2	13.8	14.4	14.6	15.3	16.2
	12H	14.3	14.9	15.1	15.7	16.7	14.3	14.9	15.1	15.7	16.7
8H	4H	12.5	13.2	13.3	14.0	15.0	12.5	13.2	13.3	14.0	15.0
	6H	13.8	14.4	14.7	15.3	16.2	13.8	14.4	14.7	15.3	16.2
	8H	14.5	15.0	15.3	15.8	16.8	14.5	15.0	15.3	15.8	16.8
	12H	15.1	15.6	16.0	16.4	17.5	15.1	15.6	16.0	16.4	17.5
12H	4H	12.6	13.2	13.4	14.0	15.0	12.6	13.2	13.4	14.0	15.0
	6H	14.0	14.5	14.8	15.3	16.3	14.0	14.5	14.8	15.3	16.3
	8H	14.7	15.1	15.5	16.0	17.0	14.7	15.1	15.5	16.0	17.0

(END OF REPORT)