

Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1245037

Luminaire Tested: PRLX-NIM-L-930-05L-U-NR

Issue Date: 1/30/2026

**Test Information**

Test Method: LM-79-2019  
Report Number: P1245037  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2412-299-1)  
Test Lab: INNOVATION CENTER  
Issue Date: 1/30/2026  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: PrentaLux  
Catalog Number: PRLX-NIM-L-930-05L-U-NR  
Description: 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, NATURAL RIBS SHADE TEXTURE  
LIGHT LEVEL 2  
Light Source: -  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 542.2 lumens  
Efficiency: N/A  
Efficacy: 36.6 lumens/watt  
Spacing Criteria (0/90/45): 0.19 / 0.19 / 0.18  
Luminous Opening: Rectangular w/ Sides (W: 0.58' x L: 0.58' x H: 1.92')  
CIE Type: General Diffuse  
  
Input Watts (W): 14.8  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 28.75 FT

TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

### Luminous Intensity Polar Plot





TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	108	108	108	108	101	101	101	101	86	86	86		73	73	73		61	61	61	56
1	95	89	83	78	87	82	77	73	70	66	62		58	55	53		48	45	43	38
2	85	76	68	61	78	70	63	57	59	54	49		49	45	42		40	37	34	30
3	77	66	57	50	71	61	53	47	52	45	40		43	38	34		35	31	28	24
4	71	58	49	42	65	54	46	40	46	39	34		38	33	29		31	27	24	20
5	65	52	43	36	60	48	40	34	41	35	30		34	29	25		28	24	21	18
6	60	47	38	32	55	44	36	30	37	31	26		31	26	22		26	22	19	16
7	56	43	34	28	51	40	32	27	34	28	23		29	24	20		24	20	17	15
8	52	39	31	25	48	36	29	24	32	25	21		27	22	18		23	19	16	13
9	49	36	28	23	45	34	27	22	29	23	19		25	20	17		21	17	15	12
10	46	33	26	21	43	31	25	20	27	22	18		24	19	16		20	16	14	12

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	23727
5°	10742
10°	2559
15°	1014
20°	642
25°	514
30°	440
35°	408
40°	410
45°	389
50°	396
55°	406
60°	419
65°	412
70°	430
75°	429
80°	432
85°	439

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 90°  
 Luminance: 449 cd/sqm

TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	31.8	5.9
10°-20°	18.1	3.3
20°-30°	17.6	3.2
30°-40°	22.5	4.2
40°-50°	29.6	5.5
50°-60°	37.1	6.8
60°-70°	44.3	8.2
70°-80°	49.3	9.1
80°-90°	50.8	9.4
90°-100°	50.8	9.4
100°-110°	49.3	9.1
110°-120°	44.0	8.1
120°-130°	36.1	6.7
130°-140°	27.6	5.1
140°-150°	18.5	3.4
150°-160°	10.2	1.9
160°-170°	4.1	0.8
170°-180°	0.5	0.1
0°-30°	67.4	12.4
0°-40°	90.0	16.6
0°-60°	156.7	28.9
0°-90°	301.1	55.5
90°-120°	144.1	26.6
90°-150°	226.3	41.7
90°-180°	241.0	44.5
0°-180°	542.2	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	750	
5°	436	32
15°	58	18
25°	37	18
35°	35	23
45°	37	30
55°	42	37
65°	44	44
75°	47	49
85°	47	38
90°	47	26
95°	47	38
105°	47	49
115°	44	44
125°	40	36
135°	35	28
145°	30	19
155°	21	10
165°	14	4
175°	2	0
180°	0	

TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	750.0
2.5°	831.5
5°	435.5
7.5°	184.0
10°	125.8
12.5°	79.2
15°	58.2
17.5°	48.9
20°	41.9
22.5°	39.6
25°	37.3
27.5°	37.3
30°	34.9
32.5°	34.9
35°	34.9
37.5°	37.3
40°	37.3
42.5°	37.3
45°	37.3
47.5°	39.6
50°	39.6
52.5°	39.6
55°	41.9
57.5°	41.9
60°	44.3
62.5°	44.3
65°	44.3
67.5°	44.3
70°	46.6
72.5°	46.6
75°	46.6
77.5°	46.6
80°	46.6
82.5°	46.6
85°	46.6
87.5°	46.6
90°	46.6
92.5°	46.6
95°	46.6
97.5°	46.6
100°	46.6
102.5°	46.6
105°	46.6
107.5°	46.6
110°	46.6



TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	44.3
115°	44.3
117.5°	44.3
120°	41.9
122.5°	41.9
125°	39.6
127.5°	39.6
130°	37.3
132.5°	37.3
135°	34.9
137.5°	34.9
140°	32.6
142.5°	30.3
145°	30.3
147.5°	27.9
150°	25.6
152.5°	23.3
155°	21.0
157.5°	21.0
160°	18.6
162.5°	16.3
165°	14.0
167.5°	11.6
170°	9.3
172.5°	7.0
175°	2.3
177.5°	0.0
180°	0.0



TEST NUMBER: P1245037

CATALOG NUMBER: PRLX-NIM-L-930-05L-U-NR

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	4.3	5.3	5.2	6.3	7.4	4.3	5.3	5.2	6.3	7.4
	3H	7.4	8.3	8.3	9.3	10.5	7.4	8.3	8.3	9.3	10.5
	4H	8.9	9.8	9.8	10.7	11.9	8.9	9.8	9.8	10.7	11.9
	6H	10.3	11.2	11.2	12.1	13.3	10.3	11.2	11.2	12.1	13.3
	8H	11.0	11.8	11.9	12.8	14.0	11.0	11.8	11.9	12.8	14.0
	12H	11.7	12.4	12.6	13.4	14.6	11.7	12.4	12.6	13.4	14.6
4H	2H	5.1	6.0	6.0	7.0	8.2	5.1	6.0	6.0	7.0	8.2
	3H	8.4	9.2	9.3	10.1	11.4	8.4	9.2	9.3	10.1	11.4
	4H	10.0	10.7	10.9	11.7	12.9	10.0	10.7	10.9	11.7	12.9
	6H	11.6	12.3	12.5	13.2	14.5	11.6	12.3	12.5	13.2	14.5
	8H	12.4	13.0	13.3	14.0	15.2	12.4	13.0	13.3	14.0	15.2
	12H	13.1	13.7	14.1	14.7	16.0	13.1	13.7	14.1	14.7	16.0
8H	4H	10.5	11.1	11.5	12.1	13.4	10.5	11.1	11.5	12.1	13.4
	6H	12.3	12.9	13.3	13.9	15.1	12.3	12.9	13.3	13.9	15.1
	8H	13.2	13.7	14.2	14.7	16.0	13.2	13.7	14.2	14.7	16.0
	12H	14.2	14.6	15.2	15.6	16.9	14.2	14.6	15.2	15.6	16.9
12H	4H	10.6	11.2	11.6	12.2	13.5	10.6	11.2	11.6	12.2	13.5
	6H	12.5	13.0	13.5	14.0	15.3	12.5	13.0	13.5	14.0	15.3
	8H	13.5	13.9	14.5	14.9	16.2	13.5	13.9	14.5	14.9	16.2

(END OF REPORT)