

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1245149

Luminaire Tested: PRLX-NIM-M-930-01L-U-NR

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1245149
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2412-299-15)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-NIM-M-930-01L-U-NR
Description: 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, NATURAL RIBS SHADE TEXTURE
LIGHT LEVEL 1
Light Source: -
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 148.7 lumens
Efficiency: N/A
Efficacy: 23.6 lumens/watt
Spacing Criteria (0/90/45): 0.2 / 0.2 / 0.18
Luminous Opening: Rectangular w/ Sides (W: 0.46' x L: 0.46' x H: 1.92')
CIE Type: General Diffuse

Input Watts (W): 6.3
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

Luminous Intensity Polar Plot





TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	108	108	108	108	101	101	101	101	86	86	86	73	73	73	61	61	61	56		
1	95	89	83	78	88	82	77	73	70	66	63	58	55	53	48	46	44	38		
2	85	76	68	62	78	70	63	58	60	54	50	50	46	42	40	37	35	30		
3	77	66	58	51	71	61	54	47	52	46	41	43	39	35	35	32	29	25		
4	71	59	50	43	65	54	46	40	46	40	35	39	34	30	32	28	25	21		
5	65	52	43	37	60	49	41	35	42	35	30	35	30	26	29	25	22	19		
6	60	47	39	32	56	44	36	30	38	32	27	32	27	23	27	23	20	17		
7	56	43	35	29	52	40	33	27	35	29	24	30	25	21	25	21	18	15		
8	53	40	32	26	49	37	30	25	32	26	22	28	23	19	23	19	17	14		
9	49	37	29	24	46	34	27	22	30	24	20	26	21	18	22	18	15	13		
10	47	34	27	22	43	32	25	21	28	22	19	24	20	17	21	17	15	13		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13422
5°	5883
10°	1135
15°	373
20°	223
25°	176
30°	159
35°	147
40°	153
45°	144
50°	137
55°	147
60°	143
65°	153
70°	151
75°	150
80°	150
85°	152

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 90°

Luminance: 154 cd/sqm

TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	10.4	7.0
10°-20°	4.8	3.2
20°-30°	4.3	2.9
30°-40°	5.9	3.9
40°-50°	8.0	5.4
50°-60°	10.2	6.8
60°-70°	12.1	8.1
70°-80°	13.3	9.0
80°-90°	13.7	9.2
90°-100°	13.7	9.2
100°-110°	13.3	9.0
110°-120°	12.4	8.3
120°-130°	10.2	6.8
130°-140°	7.7	5.2
140°-150°	4.9	3.3
150°-160°	2.8	1.9
160°-170°	0.9	0.6
170°-180°	0.1	0.1
0°-30°	19.5	13.1
0°-40°	25.4	17.1
0°-60°	43.5	29.3
0°-90°	82.7	55.6
90°-120°	39.5	26.5
90°-150°	62.2	41.8
90°-180°	66.0	44.4
0°-180°	148.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	262	
5°	156	10
15°	15	5
25°	9	4
35°	9	6
45°	10	8
55°	12	10
65°	13	12
75°	13	13
85°	13	10
90°	13	7
95°	13	10
105°	13	13
115°	13	12
125°	12	10
135°	10	8
145°	8	5
155°	6	3
165°	3	1
175°	0	0
180°	0	

TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

CANDELA DISTRIBUTION (FULL):

0°	
0°	261.9
2.5°	263.0
5°	156.2
7.5°	55.1
10°	37.9
12.5°	21.8
15°	14.9
17.5°	11.5
20°	10.3
22.5°	9.2
25°	9.2
27.5°	9.2
30°	9.2
32.5°	9.2
35°	9.2
37.5°	9.2
40°	10.3
42.5°	10.3
45°	10.3
47.5°	10.3
50°	10.3
52.5°	11.5
55°	11.5
57.5°	11.5
60°	11.5
62.5°	11.5
65°	12.6
67.5°	12.6
70°	12.6
72.5°	12.6
75°	12.6
77.5°	12.6
80°	12.6
82.5°	12.6
85°	12.6
87.5°	12.6
90°	12.6
92.5°	12.6
95°	12.6
97.5°	12.6
100°	12.6
102.5°	12.6
105°	12.6
107.5°	12.6
110°	12.6

TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

CANDELA DISTRIBUTION (continued):

	0°
112.5°	12.6
115°	12.6
117.5°	12.6
120°	11.5
122.5°	11.5
125°	11.5
127.5°	11.5
130°	10.3
132.5°	10.3
135°	10.3
137.5°	9.2
140°	9.2
142.5°	8.0
145°	8.0
147.5°	6.9
150°	6.9
152.5°	6.9
155°	5.7
157.5°	5.7
160°	4.6
162.5°	3.4
165°	3.4
167.5°	2.3
170°	2.3
172.5°	1.1
175°	0.0
177.5°	0.0
180°	0.0

TEST NUMBER: P1245149

CATALOG NUMBER: PRLX-NIM-M-930-01L-U-NR

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.7	1.8	1.6	2.7	3.9	0.7	1.8	1.6	2.7	3.9
	3H	3.9	4.8	4.8	5.7	6.9	3.9	4.8	4.8	5.7	6.9
	4H	5.3	6.2	6.2	7.1	8.3	5.3	6.2	6.2	7.1	8.3
	6H	6.7	7.5	7.6	8.5	9.7	6.7	7.5	7.6	8.5	9.7
	8H	7.3	8.2	8.3	9.1	10.3	7.3	8.2	8.3	9.1	10.3
	12H	8.0	8.8	8.9	9.7	11.0	8.0	8.8	8.9	9.7	11.0
4H	2H	1.6	2.5	2.5	3.4	4.6	1.6	2.5	2.5	3.4	4.6
	3H	4.8	5.6	5.8	6.6	7.8	4.8	5.6	5.8	6.6	7.8
	4H	6.4	7.1	7.3	8.1	9.3	6.4	7.1	7.3	8.1	9.3
	6H	8.0	8.6	8.9	9.6	10.8	8.0	8.6	8.9	9.6	10.8
	8H	8.7	9.3	9.6	10.3	11.6	8.7	9.3	9.6	10.3	11.6
	12H	9.5	10.0	10.4	11.0	12.3	9.5	10.0	10.4	11.0	12.3
8H	4H	6.9	7.5	7.8	8.5	9.8	6.9	7.5	7.8	8.5	9.8
	6H	8.7	9.2	9.6	10.2	11.5	8.7	9.2	9.6	10.2	11.5
	8H	9.6	10.0	10.5	11.0	12.3	9.6	10.0	10.5	11.0	12.3
	12H	10.5	10.9	11.5	11.9	13.2	10.5	10.9	11.5	11.9	13.2
12H	4H	7.0	7.6	8.0	8.6	9.8	7.0	7.6	8.0	8.6	9.8
	6H	8.8	9.3	9.8	10.3	11.6	8.8	9.3	9.8	10.3	11.6
	8H	9.8	10.2	10.8	11.2	12.6	9.8	10.2	10.8	11.2	12.6

(END OF REPORT)