

Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1245335

Luminaire Tested: PRLX-UNA-L-935-02L-U-NL

Issue Date: 1/30/2026

Test Information

Test Method: LM-79-2019
Report Number: P1245335
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G2-2412-299-10)
Test Lab: INNOVATION CENTER
Issue Date: 1/30/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UNA-L-935-02L-U-NL
Description: 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, NATURAL LINES SHADE TEXTUF
LIGHT LEVEL 1
Light Source: -
Ballast/Driver: -


Summary

Lumens per Lamp: N/A
Luminaire Lumens: 210.1 lumens
Efficiency: N/A
Efficacy: 37.5 lumens/watt
Spacing Criteria (0/90/45): 0.2 / 0.2 / 0.2
Luminous Opening: Rectangular w/ Sides (W: 0.58' x L: 0.58' x H: 1.92')
CIE Type: General Diffuse

Input Watts (W): 5.6
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 28.75 FT

TEST NUMBER: P1245335
CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

Luminous Intensity Polar Plot





TEST NUMBER: P1245335

CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	109	109	109	109	101	101	101	101	87	87	87	74	74	74	62	62	62	57
1	96	90	85	80	88	83	79	75	71	68	64	60	57	55	49	47	46	40
2	86	77	70	63	80	72	65	59	61	56	51	51	47	44	42	39	37	32
3	79	68	59	52	72	63	55	49	54	48	43	45	40	37	37	34	31	27
4	72	60	51	44	66	56	48	42	48	41	37	40	35	31	33	30	27	23
5	66	54	45	38	61	50	42	36	43	37	32	36	31	28	30	27	23	20
6	61	48	40	34	57	45	37	32	39	33	28	33	28	25	28	24	21	18
7	57	44	36	30	53	41	34	28	36	30	25	31	26	22	26	22	19	17
8	53	41	33	27	49	38	31	26	33	27	23	29	24	20	24	21	18	15
9	50	37	30	25	46	35	28	23	31	25	21	27	22	19	23	19	16	14
10	47	35	27	22	44	33	26	21	29	23	19	25	21	17	22	18	15	13

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	8934
5°	4188
10°	1178
15°	554
20°	365
25°	270
30°	223
35°	194
40°	176
45°	165
50°	157
55°	153
60°	150
65°	150
70°	149
75°	150
80°	148
85°	151

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 165 cd/sqm

TEST NUMBER: P1245335

CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	12.6	6.0
10°-20°	9.4	4.5
20°-30°	9.2	4.4
30°-40°	10.5	5.0
40°-50°	12.2	5.8
50°-60°	14.2	6.8
60°-70°	16.0	7.6
70°-80°	17.2	8.2
80°-90°	17.5	8.3
90°-100°	17.9	8.5
100°-110°	17.5	8.3
110°-120°	16.0	7.6
120°-130°	13.7	6.5
130°-140°	10.8	5.1
140°-150°	7.7	3.7
150°-160°	4.9	2.3
160°-170°	2.4	1.1
170°-180°	0.5	0.2
0°-30°	31.2	14.9
0°-40°	41.7	19.9
0°-60°	68.1	32.4
0°-90°	118.8	56.5
90°-120°	51.4	24.5
90°-150°	83.6	39.8
90°-180°	91.0	43.3
0°-180°	210.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	282	
5°	170	13
15°	32	9
25°	20	9
35°	17	10
45°	16	12
55°	16	14
65°	16	16
75°	16	17
85°	16	13
90°	16	9
95°	16	13
105°	17	18
115°	16	16
125°	15	14
135°	14	11
145°	12	8
155°	10	5
165°	8	2
175°	4	0
180°	3	

TEST NUMBER: P1245335

CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

CANDELA DISTRIBUTION (FULL):

	0°
0°	282.4
2.5°	306.5
5°	169.8
7.5°	78.7
10°	57.9
12.5°	39.8
15°	31.8
17.5°	27.1
20°	23.8
22.5°	21.3
25°	19.6
27.5°	18.5
30°	17.7
32.5°	17.1
35°	16.6
37.5°	16.3
40°	16.0
42.5°	15.9
45°	15.8
47.5°	15.7
50°	15.7
52.5°	15.8
55°	15.8
57.5°	15.9
60°	15.9
62.5°	16.0
65°	16.1
67.5°	16.2
70°	16.2
72.5°	16.3
75°	16.3
77.5°	16.2
80°	16.0
82.5°	16.0
85°	16.0
87.5°	16.1
90°	16.2
92.5°	16.3
95°	16.4
97.5°	16.5
100°	16.6
102.5°	16.6
105°	16.6
107.5°	16.5
110°	16.4



TEST NUMBER: P1245335

CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

CANDELA DISTRIBUTION (continued):

	0°
112.5°	16.3
115°	16.2
117.5°	16.0
120°	15.8
122.5°	15.5
125°	15.2
127.5°	14.9
130°	14.7
132.5°	14.3
135°	13.9
137.5°	13.5
140°	13.1
142.5°	12.7
145°	12.2
147.5°	11.8
150°	11.4
152.5°	10.9
155°	10.4
157.5°	10.0
160°	9.4
162.5°	8.9
165°	8.3
167.5°	7.5
170°	6.6
172.5°	5.5
175°	4.3
177.5°	3.2
180°	2.8



TEST NUMBER: P1245335

CATALOG NUMBER: PRLX-UNA-L-935-02L-U-NL

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room Dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.9	1.9	1.8	2.8	4.0	0.9	1.9	1.8	2.8	4.0
	3H	3.7	4.7	4.6	5.6	6.8	3.7	4.7	4.6	5.6	6.8
	4H	5.1	6.0	6.0	6.9	8.1	5.1	6.0	6.0	6.9	8.1
	6H	6.5	7.3	7.4	8.2	9.4	6.5	7.3	7.4	8.2	9.4
	8H	7.1	7.9	8.0	8.9	10.1	7.1	7.9	8.0	8.9	10.1
	12H	7.7	8.5	8.7	9.4	10.7	7.7	8.5	8.7	9.4	10.7
4H	2H	1.6	2.5	2.5	3.4	4.6	1.6	2.5	2.5	3.4	4.6
	3H	4.7	5.4	5.6	6.4	7.6	4.7	5.4	5.6	6.4	7.6
	4H	6.2	6.9	7.1	7.9	9.1	6.2	6.9	7.1	7.9	9.1
	6H	7.7	8.3	8.6	9.3	10.6	7.7	8.3	8.6	9.3	10.6
	8H	8.4	9.0	9.4	10.0	11.3	8.4	9.0	9.4	10.0	11.3
	12H	9.2	9.7	10.1	10.7	12.0	9.2	9.7	10.1	10.7	12.0
8H	4H	6.7	7.3	7.6	8.3	9.5	6.7	7.3	7.6	8.3	9.5
	6H	8.4	8.9	9.4	9.9	11.2	8.4	8.9	9.4	9.9	11.2
	8H	9.3	9.7	10.2	10.7	12.0	9.3	9.7	10.2	10.7	12.0
	12H	10.2	10.6	11.2	11.6	12.9	10.2	10.6	11.2	11.6	12.9
12H	4H	6.8	7.3	7.8	8.3	9.6	6.8	7.3	7.8	8.3	9.6
	6H	8.6	9.0	9.5	10.0	11.3	8.6	9.0	9.5	10.0	11.3
	8H	9.5	9.9	10.5	10.9	12.2	9.5	9.9	10.5	10.9	12.2

(END OF REPORT)