

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1503775

Luminaire Tested: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1503775
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-13)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)
Description: PrentaLux Fluxyn SM4 SURFACE MOUNT, DISC, OPEN CYLINDER, WHITE REFLECTOR
LIGHT LEVEL 2 - 800 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 2700K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 615.9 lumens
Efficiency: N/A
Efficacy: 74.2 lumens/watt
Spacing Criteria (0/90/45): 1.07 / 1.07 / 1.14
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 8.3
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1503775

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1503775

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20				
RC	80				70				50				30				10				0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0			
RCR																					
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100			
1	110	106	103	99	108	104	101	98	100	97	95	96	94	92	93	91	89	87			
2	102	95	89	84	99	93	88	83	90	85	81	86	83	79	83	80	78	76			
3	94	85	78	72	92	83	77	71	81	75	70	78	73	69	75	71	68	66			
4	87	77	69	63	85	75	68	62	73	67	62	71	65	61	69	64	60	58			
5	81	69	61	55	79	68	61	55	66	60	55	64	59	54	63	58	53	52			
6	75	63	55	49	74	62	55	49	61	54	49	59	53	48	58	52	48	46			
7	70	58	50	44	69	57	50	44	56	49	44	54	48	44	53	48	43	42			
8	66	53	46	40	64	53	45	40	51	45	40	50	44	40	49	44	39	38			
9	62	49	42	37	60	49	42	37	48	41	36	47	41	36	46	40	36	34			
10	58	46	39	34	57	45	38	34	44	38	33	44	38	33	43	37	33	32			

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	10216
5°	10175
10°	10095
15°	9766
20°	9287
25°	8768
30°	8179
35°	7548
40°	6847
45°	6088
50°	5239
55°	4365
60°	3522
65°	3152
70°	2975
75°	2716
80°	2486
85°	2229

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 6088 cd/sqm

TEST NUMBER: P1503775

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	31.2	5.1
10°-20°	85.7	13.9
20°-30°	118.4	19.2
30°-40°	125.1	20.3
40°-50°	107.5	17.4
50°-60°	73.1	11.9
60°-70°	43.2	7.0
70°-80°	24.6	4.0
80°-90°	7.1	1.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	235.4	38.2
0°-40°	360.5	58.5
0°-60°	541.1	87.9
0°-90°	615.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	615.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	331	
5°	329	31
15°	306	86
25°	258	118
35°	200	125
45°	140	107
55°	81	73
65°	43	43
75°	23	25
85°	6	7
90°	0	

TEST NUMBER: P1503775

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OC (2700K-800LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	331.3
2.5°	330.0
5°	328.7
7.5°	327.5
10°	322.4
12.5°	314.8
15°	305.9
17.5°	294.5
20°	283.0
22.5°	270.3
25°	257.7
27.5°	245.0
30°	229.7
32.5°	215.8
35°	200.5
37.5°	185.3
40°	170.1
42.5°	154.8
45°	139.6
47.5°	124.4
50°	109.2
52.5°	95.2
55°	81.2
57.5°	68.5
60°	57.1
62.5°	48.2
65°	43.2
67.5°	38.1
70°	33.0
72.5°	27.9
75°	22.8
77.5°	19.0
80°	14.0
82.5°	10.2
85°	6.3
87.5°	2.5
90°	0.0

(END OF REPORT)