

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1503824

Luminaire Tested: PRLX-SM4-03-LS-FS-D2W-XXXX-BRNZ-XX-OC (3500K-1000LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1503824
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-14)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM4-03-LS-FS-D2W-XXXX-BRNZ-XX-OC (3500K-1000LM)
Description: PrentaLux Fluxyn SM4 SURFACE MOUNT, DISC, OPEN CYLINDER, BRONZE REFLECTOR
LIGHT LEVEL 3 - 1000 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 3500K CCT, 90 CRI - DIM TO WARM (1800K)
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 768.4 lumens
Efficiency: N/A
Efficacy: 66.8 lumens/watt
Spacing Criteria (0/90/45): 1.06 / 1.06 / 1.14
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 11.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1503824

CATALOG NUMBER: PRLX-SM4-03-LS-FS-D2W-XXXX-BRNZ-XX-OC (3500K-1000LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1503824

CATALOG NUMBER: PRLX-SM4-03-LS-FS-D2W-XXXX-BRNZ-XX-OC (3500K-1000LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	40.2	5.2
10°-20°	110.0	14.3
20°-30°	151.3	19.7
30°-40°	158.4	20.6
40°-50°	133.5	17.4
50°-60°	87.0	11.3
60°-70°	49.8	6.5
70°-80°	29.5	3.8
80°-90°	8.7	1.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	301.5	39.2
0°-40°	460.0	59.9
0°-60°	680.4	88.6
0°-90°	768.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	768.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	424	
5°	422	40
15°	392	110
25°	330	151
35°	254	158
45°	174	133
55°	96	87
65°	50	50
75°	28	29
85°	7	9
90°	0	

TEST NUMBER: P1503824

CATALOG NUMBER: PRLX-SM4-03-LS-FS-D2W-XXXX-BRNZ-XX-OC (3500K-1000LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	424.1
2.5°	424.1
5°	422.3
7.5°	422.3
10°	415.2
12.5°	404.6
15°	392.2
17.5°	378.0
20°	362.0
22.5°	346.0
25°	330.1
27.5°	312.3
30°	292.8
32.5°	273.3
35°	253.7
37.5°	234.2
40°	214.7
42.5°	193.4
45°	173.9
47.5°	152.6
50°	133.1
52.5°	115.3
55°	95.8
57.5°	79.9
60°	65.7
62.5°	55.0
65°	49.7
67.5°	44.4
70°	39.0
72.5°	33.7
75°	28.4
77.5°	21.3
80°	17.7
82.5°	12.4
85°	7.1
87.5°	3.5
90°	0.0

(END OF REPORT)