

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1503769

Luminaire Tested: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1503769
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-7)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)
Description: PrentaLux Fluxyn SM4 SURFACE MOUNT, DISC, NO DIFFUSER, WHITE REFLECTOR
LIGHT LEVEL 2 - 800 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 4000K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 698.5 lumens
Efficiency: N/A
Efficacy: 85.2 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.3
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 8.2
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1503769

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1503769

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88		
2	102	95	89	84	100	93	88	83	90	85	81	87	83	80	84	81	78	76		
3	94	85	78	72	92	83	77	72	81	75	70	78	73	69	76	71	68	66		
4	87	76	69	63	85	75	68	62	73	66	61	70	65	61	68	64	60	58		
5	81	69	61	55	79	68	60	55	66	59	54	64	58	53	62	57	53	51		
6	75	63	54	49	73	62	54	48	60	53	48	58	52	48	57	51	47	45		
7	70	57	49	43	68	56	49	43	55	48	43	53	47	43	52	47	42	41		
8	65	52	44	39	63	52	44	39	50	44	39	49	43	38	48	42	38	36		
9	61	48	41	35	59	48	40	35	47	40	35	46	39	35	45	39	35	33		
10	57	45	37	32	56	44	37	32	43	37	32	42	36	32	41	36	32	30		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	9791
5°	9788
10°	9747
15°	9699
20°	9641
25°	9530
30°	9400
35°	9185
40°	8671
45°	7928
50°	6927
55°	5758
60°	4299
65°	2816
70°	2245
75°	2228
80°	2220
85°	1769

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 7928 cd/sqm

TEST NUMBER: P1503769

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	30.0	4.3
10°-20°	85.8	12.3
20°-30°	129.0	18.5
30°-40°	151.6	21.7
40°-50°	139.4	20.0
50°-60°	95.4	13.7
60°-70°	41.4	5.9
70°-80°	19.7	2.8
80°-90°	6.1	0.9
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	244.8	35.0
0°-40°	396.4	56.7
0°-60°	631.2	90.4
0°-90°	698.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	698.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	318	
5°	316	30
15°	304	86
25°	280	129
35°	244	152
45°	182	139
55°	107	95
65°	39	41
75°	19	20
85°	5	6
90°	0	

TEST NUMBER: P1503769

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-ND (4000K-800LM)

CANDELA DISTRIBUTION (FULL):

0°	
0°	317.5
2.5°	316.2
5°	316.2
7.5°	313.8
10°	311.3
12.5°	308.8
15°	303.8
17.5°	298.8
20°	293.8
22.5°	286.4
25°	280.1
27.5°	272.7
30°	264.0
32.5°	255.2
35°	244.0
37.5°	230.3
40°	215.4
42.5°	199.2
45°	181.8
47.5°	163.1
50°	144.4
52.5°	125.8
55°	107.1
57.5°	88.4
60°	69.7
62.5°	53.5
65°	38.6
67.5°	28.6
70°	24.9
72.5°	21.2
75°	18.7
77.5°	16.2
80°	12.5
82.5°	8.7
85°	5.0
87.5°	2.5
90°	0.0

(END OF REPORT)