

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1503798

Luminaire Tested: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1503798
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-10)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)
Description: PrentaLux Fluxyn SM4 SURFACE MOUNT, DISC, OPEN TAPERED, WHITE REFLECTOR
LIGHT LEVEL 1 - 650 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 4000K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 382.7 lumens
Efficiency: N/A
Efficacy: 58.9 lumens/watt
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.17
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct

Input Watts (W): 6.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1503798

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1503798

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20				
RC	80					70					50					30					10				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10		
RCR																									
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100							
1	110	105	101	98	107	103	99	96	99	96	93	95	92	90	91	89	87	85							
2	101	93	87	81	98	91	85	80	87	83	78	84	80	77	81	78	75	73							
3	92	83	75	69	90	81	74	68	78	72	67	75	70	66	73	69	65	63							
4	85	74	66	60	83	73	65	59	70	64	58	68	62	58	66	61	57	55							
5	79	67	59	52	77	66	58	52	64	57	52	62	56	51	60	55	50	48							
6	73	61	53	46	72	60	52	46	58	51	46	57	50	46	55	49	45	43							
7	68	56	47	42	67	55	47	42	53	46	41	52	46	41	51	45	41	39							
8	64	51	43	38	63	51	43	38	49	42	37	48	42	37	47	41	37	35							
9	60	47	40	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32							
10	57	44	36	31	55	43	36	31	42	36	31	42	35	31	41	35	31	29							

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	5665
5°	5665
10°	5649
15°	5596
20°	5401
25°	5131
30°	4782
35°	4393
40°	3973
45°	3537
50°	3089
55°	2726
60°	2609
65°	2627
70°	2633
75°	2609
80°	2451
85°	2123

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 3537 cd/sqm

TEST NUMBER: P1503798

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	17.4	4.5
10°-20°	49.1	12.8
20°-30°	69.1	18.1
30°-40°	72.9	19.0
40°-50°	62.6	16.4
50°-60°	46.3	12.1
60°-70°	35.5	9.3
70°-80°	22.9	6.0
80°-90°	6.9	1.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	135.7	35.4
0°-40°	208.5	54.5
0°-60°	317.4	82.9
0°-90°	382.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	382.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	184	
5°	183	17
15°	175	49
25°	151	69
35°	117	73
45°	81	63
55°	51	46
65°	36	36
75°	22	23
85°	6	7
90°	0	

TEST NUMBER: P1503798

CATALOG NUMBER: PRLX-SM4-03-LS-FS-010-XXXX-WHTE-XX-OT (4000K-650LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	183.7
2.5°	183.5
5°	183.0
7.5°	181.9
10°	180.4
12.5°	178.4
15°	175.3
17.5°	170.5
20°	164.6
22.5°	158.0
25°	150.8
27.5°	142.8
30°	134.3
32.5°	125.5
35°	116.7
37.5°	108.0
40°	98.7
42.5°	90.0
45°	81.1
47.5°	72.7
50°	64.4
52.5°	57.3
55°	50.7
57.5°	45.8
60°	42.3
62.5°	39.0
65°	36.0
67.5°	32.7
70°	29.2
72.5°	25.7
75°	21.9
77.5°	17.9
80°	13.8
82.5°	9.9
85°	6.0
87.5°	2.4
90°	0.0

(END OF REPORT)