

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504017

Luminaire Tested: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504017
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-21)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)
Description: PrentaLux Fluxyn SM6 SURFACE MOUNT, DISC, OPEN TAPERED, BRASS REFLECTOR
LIGHT LEVEL 1 - 750 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 3000K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 526.6 lumens
Efficiency: N/A
Efficacy: 75.2 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.22
Luminous Opening: Circular (Dia: 1.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504017

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)

Luminous Intensity Polar Plot



TEST NUMBER: P1504017

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20						20
RC	80					70					50					30						10
RW	70	50	30	10		70	50	30	10		50	30	10		50	30	10		50	30	10	
RCR																						
0	119	119	119	119		116	116	116	116		111	111	111		106	106	106		102	102	102	
1	109	105	101	97		107	103	99	96		99	96	93		95	92	90		91	89	87	
2	100	93	86	81		98	91	85	80		87	82	78		84	80	76		81	78	75	
3	92	82	75	69		90	81	74	68		78	72	67		75	70	66		73	68	65	
4	85	74	65	59		83	72	65	59		70	63	58		68	62	57		66	61	56	
5	79	66	58	52		77	65	57	51		63	56	51		61	55	50		60	54	50	
6	73	60	52	46		71	59	51	46		58	51	45		56	50	45		54	49	44	
7	68	55	47	41		66	54	46	41		53	46	41		51	45	40		50	44	40	
8	64	51	42	37		62	50	42	37		49	42	37		47	41	36		46	40	36	
9	60	47	39	34		58	46	39	33		45	38	33		44	38	33		43	37	33	
10	56	43	36	31		55	43	35	31		42	35	30		41	35	30		40	34	30	

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2376
5°	2375
10°	2382
15°	2366
20°	2336
25°	2244
30°	2116
35°	1979
40°	1840
45°	1680
50°	1488
55°	1317
60°	1148
65°	1144
70°	1178
75°	1167
80°	1102
85°	1040

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 1680 cd/sqm

TEST NUMBER: P1504017

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	22.4	4.2
10°-20°	64.0	12.1
20°-30°	92.7	17.6
30°-40°	100.8	19.1
40°-50°	90.8	17.2
50°-60°	67.2	12.8
60°-70°	47.7	9.1
70°-80°	31.5	6.0
80°-90°	9.7	1.8
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	179.0	34.0
0°-40°	279.8	53.1
0°-60°	437.8	83.1
0°-90°	526.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	526.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	236	
5°	235	22
15°	227	64
25°	202	93
35°	161	101
45°	118	91
55°	75	67
65°	48	48
75°	30	32
85°	9	10
90°	0	

TEST NUMBER: P1504017

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-OT (3000K-750LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	236
2.5°	236
5°	235
7.5°	234
10°	233
12.5°	230
15°	227
17.5°	223
20°	218
22.5°	210
25°	202
27.5°	193
30°	182
32.5°	172
35°	161
37.5°	151
40°	140
42.5°	129
45°	118
47.5°	107
50°	95
52.5°	85
55°	75
57.5°	65
60°	57
62.5°	52
65°	48
67.5°	44
70°	40
72.5°	35
75°	30
77.5°	25
80°	19
82.5°	14
85°	9
87.5°	3
90°	0

(END OF REPORT)