

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504048

Luminaire Tested: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504048
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-22)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)
Description: PrentaLux Fluxyn SM6 SURFACE MOUNT, DISC, OPEN CYLINDER, WHITE REFLECTOR
LIGHT LEVEL 2 - 900 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 3000K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 861.4 lumens
Efficiency: N/A
Efficacy: 101.3 lumens/watt
Spacing Criteria (0/90/45): 1.1 / 1.1 / 1.19
Luminous Opening: Circular (Dia: 1.17' x H: 0')
CIE Type: Direct

Input Watts (W): 8.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504048

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1504048

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	110	106	102	99	108	104	100	97	100	97	94	96	94	91	92	90	89	87		
2	102	94	88	83	99	92	87	82	89	84	80	86	82	79	83	80	77	75		
3	94	84	77	71	91	83	76	71	80	74	69	77	72	68	75	71	67	65		
4	87	76	68	62	84	74	67	61	72	66	61	70	64	60	68	63	59	57		
5	80	69	60	54	78	67	60	54	65	59	53	64	58	53	62	57	52	50		
6	75	62	54	48	73	61	54	48	60	53	48	58	52	47	57	51	47	45		
7	70	57	49	43	68	56	49	43	55	48	43	53	47	43	52	47	42	40		
8	65	52	45	39	64	52	44	39	50	44	39	49	43	39	48	43	38	37		
9	61	48	41	36	60	48	41	35	47	40	35	46	40	35	45	39	35	33		
10	57	45	38	33	56	44	37	32	43	37	32	43	37	32	42	36	32	30		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	4349
5°	4365
10°	4342
15°	4216
20°	4026
25°	3855
30°	3645
35°	3398
40°	3161
45°	2862
50°	2530
55°	2142
60°	1734
65°	1453
70°	1410
75°	1350
80°	1247
85°	1109

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2862 cd/sqm

TEST NUMBER: P1504048

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	41.0	4.8
10°-20°	113.5	13.2
20°-30°	159.3	18.5
30°-40°	172.8	20.1
40°-50°	154.8	18.0
50°-60°	109.8	12.7
60°-70°	62.7	7.3
70°-80°	36.3	4.2
80°-90°	11.1	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	313.9	36.4
0°-40°	486.7	56.5
0°-60°	751.3	87.2
0°-90°	861.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	861.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	432	
5°	432	41
15°	404	114
25°	347	159
35°	276	173
45°	201	155
55°	122	110
65°	61	63
75°	35	36
85°	10	11
90°	0	

TEST NUMBER: P1504048

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-WHTE-XX-OC (3000K-900LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	431.9
2.5°	431.9
5°	431.9
7.5°	430.7
10°	424.7
12.5°	416.3
15°	404.4
17.5°	391.2
20°	375.7
22.5°	362.5
25°	347.0
27.5°	330.2
30°	313.5
32.5°	294.3
35°	276.4
37.5°	258.4
40°	240.5
42.5°	220.1
45°	201.0
47.5°	181.9
50°	161.5
52.5°	142.4
55°	122.0
57.5°	104.1
60°	86.1
62.5°	71.8
65°	61.0
67.5°	53.8
70°	47.9
72.5°	40.7
75°	34.7
77.5°	27.5
80°	21.5
82.5°	15.6
85°	9.6
87.5°	4.8
90°	0.0

(END OF REPORT)