

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504121

Luminaire Tested: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504121
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-18)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)
Description: PrentaLux Fluxyn SM6 SURFACE MOUNT, DISC, NO DIFFUSER, BRASS REFLECTOR
LIGHT LEVEL 3 - 1200 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 3000K CCT, 90 CRI - DIM TO WARM (1800K)
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1319.6 lumens
Efficiency: N/A
Efficacy: 94.3 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.36
Luminous Opening: Circular (Dia: 1.17' x H: 0')
CIE Type: Direct

Input Watts (W): 14
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504121

CATALOG NUMBER: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1504121

CATALOG NUMBER: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	109	105	102	99	101	98	96	97	95	93	94	92	91	89		
2	103	96	90	85	100	94	89	84	91	86	83	87	84	81	85	82	79	77		
3	95	86	79	73	92	84	78	73	81	76	71	79	74	70	76	72	69	67		
4	87	77	69	63	85	76	68	63	73	67	62	71	66	61	69	64	60	58		
5	81	69	61	55	79	68	61	55	66	60	54	64	58	54	63	57	53	51		
6	75	63	55	49	73	62	54	49	60	53	48	58	52	48	57	52	47	45		
7	70	57	49	43	68	56	49	43	55	48	43	53	47	43	52	47	42	40		
8	65	52	44	39	63	52	44	39	50	43	39	49	43	38	48	42	38	36		
9	61	48	40	35	59	47	40	35	46	40	35	45	39	35	44	39	35	33		
10	57	44	37	32	56	44	37	32	43	36	32	42	36	32	41	36	31	30		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	5866
5°	5850
10°	5841
15°	5818
20°	5779
25°	5718
30°	5656
35°	5585
40°	5502
45°	5343
50°	4843
55°	4104
60°	3075
65°	1796
70°	556
75°	292
80°	331
85°	439

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 5343 cd/sqm

TEST NUMBER: P1504121

CATALOG NUMBER: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	55.0	4.2
10°-20°	157.5	11.9
20°-30°	237.3	18.0
30°-40°	284.1	21.5
40°-50°	286.5	21.7
50°-60°	207.8	15.7
60°-70°	78.0	5.9
70°-80°	9.7	0.7
80°-90°	3.9	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	449.8	34.1
0°-40°	733.9	55.6
0°-60°	1228.1	93.1
0°-90°	1319.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1319.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	583	
5°	579	55
15°	558	158
25°	515	237
35°	454	284
45°	375	286
55°	234	208
65°	75	78
75°	8	10
85°	4	4
90°	0	

TEST NUMBER: P1504121

CATALOG NUMBER: PRLX-SM6-03-LS-FS-D2W-XXXX-BRSS-XX-ND (3000K-1200LM)

CANDELA DISTRIBUTION (FULL):

	0°
0°	582.6
2.5°	580.7
5°	578.8
7.5°	575.1
10°	571.3
12.5°	567.5
15°	558.1
17.5°	548.7
20°	539.3
22.5°	527.9
25°	514.7
27.5°	501.5
30°	486.5
32.5°	469.5
35°	454.4
37.5°	437.4
40°	418.6
42.5°	401.6
45°	375.2
47.5°	345.0
50°	309.2
52.5°	273.4
55°	233.8
57.5°	194.2
60°	152.7
62.5°	113.1
65°	75.4
67.5°	43.4
70°	18.9
72.5°	9.4
75°	7.5
77.5°	7.5
80°	5.7
82.5°	5.7
85°	3.8
87.5°	1.9
90°	0.0

(END OF REPORT)