

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1503990

Luminaire Tested: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)

Issue Date: 7/28/2026

Test Information

Test Method: LM-79-2024
Report Number: P1503990
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2606-836-18)
Test Lab: INNOVATION CENTER
Issue Date: 7/28/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)
Description: PrentaLux Fluxyn SM6 SURFACE MOUNT, DISC, NO DIFFUSER, BRASS REFLECTOR
LIGHT LEVEL 1 - 750 NOMINAL LUMENS
Light Source: SELECTABLE CCT - 3500K CCT, 90 CRI
Ballast/Driver: ELECTRONIC DRIVER

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 702.6 lumens
Efficiency: N/A
Efficacy: 100.4 lumens/watt
Spacing Criteria (0/90/45): 1.24 / 1.24 / 1.36
Luminous Opening: Circular (Dia: 1.17' x H: 0')
CIE Type: Direct

Input Watts (W): 7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1503990

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)

Luminous Intensity Polar Plot





TEST NUMBER: P1503990

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	107	104	101	109	105	102	99	101	98	96	97	95	93	94	92	91	89		
2	103	96	90	85	100	94	89	85	91	86	83	87	84	81	85	82	79	77		
3	95	86	79	73	92	84	78	73	81	76	71	79	74	70	76	72	69	67		
4	87	77	69	63	85	76	68	63	73	67	62	71	66	61	69	64	60	58		
5	81	69	61	55	79	68	61	55	66	60	54	64	58	54	63	57	53	51		
6	75	63	55	49	73	62	54	49	60	53	48	58	52	48	57	52	47	45		
7	70	57	49	43	68	56	49	43	55	48	43	53	47	43	52	47	42	40		
8	65	52	44	39	63	52	44	39	50	43	39	49	43	38	48	42	38	36		
9	61	48	40	35	59	47	40	35	46	40	35	45	39	35	44	39	35	33		
10	57	44	37	32	56	44	37	32	43	36	32	42	36	32	41	36	31	30		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3123
5°	3115
10°	3110
15°	3098
20°	3076
25°	3045
30°	3011
35°	2975
40°	2930
45°	2845
50°	2578
55°	2186
60°	1637
65°	958
70°	294
75°	156
80°	174
85°	231

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 2845 cd/sqm

TEST NUMBER: P1503990

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.3	4.2
10°-20°	83.9	11.9
20°-30°	126.4	18.0
30°-40°	151.3	21.5
40°-50°	152.5	21.7
50°-60°	110.6	15.7
60°-70°	41.5	5.9
70°-80°	5.1	0.7
80°-90°	2.0	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	239.5	34.1
0°-40°	390.8	55.6
0°-60°	653.9	93.1
0°-90°	702.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	702.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	310	
5°	308	29
15°	297	84
25°	274	126
35°	242	151
45°	200	153
55°	124	111
65°	40	42
75°	4	5
85°	2	2
90°	0	

TEST NUMBER: P1503990

CATALOG NUMBER: PRLX-SM6-03-LS-FS-010-XXXX-BRSS-XX-ND (3500K-750LM)

CANDELA DISTRIBUTION (FULL):

0°	
0°	310.2
2.5°	309.2
5°	308.2
7.5°	306.2
10°	304.2
12.5°	302.2
15°	297.2
17.5°	292.2
20°	287.1
22.5°	281.1
25°	274.1
27.5°	267.1
30°	259.0
32.5°	250.0
35°	242.0
37.5°	232.9
40°	222.9
42.5°	213.8
45°	199.8
47.5°	183.7
50°	164.6
52.5°	145.6
55°	124.5
57.5°	103.4
60°	81.3
62.5°	60.2
65°	40.2
67.5°	23.1
70°	10.0
72.5°	5.0
75°	4.0
77.5°	4.0
80°	3.0
82.5°	3.0
85°	2.0
87.5°	1.0
90°	0.0

(END OF REPORT)