

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504579

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504579
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-29)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)
Description: PrentaLux UHBS2 4-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, CONIC BLACK SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 18,000 LUMENS
Light Source: 3000K CCT, 80 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 14928.0 lumens
Efficiency: N/A
Efficacy: 121.5 lumens/watt
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.12
Luminous Opening: Circular (Dia: 1.26' x H: 0')
CIE Type: Direct

Input Watts (W): 122.9
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504579

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)

Luminous Intensity Polar Plot





TEST NUMBER: P1504579

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20					20					20					20					20				
RC	80					70					50					30					10				
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10	50	30	10		
RCR																									
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100							
1	113	109	106	104	110	107	105	102	103	101	99	99	98	96	96	95	93	91							
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	87	84	83							
3	99	91	85	81	97	90	84	80	87	83	79	85	81	77	82	79	76	74							
4	93	84	77	72	91	82	76	72	80	75	71	78	73	70	76	72	69	67							
5	87	77	70	65	85	76	69	64	74	68	64	72	67	63	70	66	63	61							
6	81	71	64	59	80	70	63	58	68	62	58	67	61	57	65	61	57	55							
7	76	65	58	53	75	65	58	53	63	57	53	62	56	52	61	56	52	50							
8	72	60	53	49	70	60	53	49	59	53	48	58	52	48	57	52	48	46							
9	67	56	49	45	66	56	49	45	55	49	44	54	48	44	53	48	44	43							
10	64	52	46	41	63	52	46	41	51	45	41	50	45	41	49	44	41	39							

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	86078
5°	86183
10°	85787
15°	84826
20°	82072
25°	78465
30°	72895
35°	64365
40°	52362
45°	40583
50°	32026
55°	16427
60°	5737
65°	2484
70°	739
75°	375
80°	394
85°	447

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 40583 cd/sqm

TEST NUMBER: P1504579

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	941.9	6.3
10°-20°	2656.7	17.8
20°-30°	3762.2	25.2
30°-40°	3764.3	25.2
40°-50°	2604.0	17.4
50°-60°	1040.1	7.0
60°-70°	140.1	0.9
70°-80°	14.0	0.1
80°-90°	4.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	7360.7	49.3
0°-40°	11125.0	74.5
0°-60°	14769.1	98.9
0°-90°	14928.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	14928.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	9945	
5°	9919	942
15°	9466	2657
25°	8216	3762
35°	6092	3764
45°	3315	2604
55°	1089	1040
65°	121	140
75°	11	14
85°	4	5
90°	0	

TEST NUMBER: P1504579

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-B-04-BLAK-PS (3000K_L18_Medium_120V)

CANDELA DISTRIBUTION (FULL):

	0°
0°	9945.0
2.5°	9922.5
5°	9919.2
7.5°	9869.7
10°	9760.8
12.5°	9636.1
15°	9466.4
17.5°	9221.5
20°	8910.3
22.5°	8578.9
25°	8216.0
27.5°	7801.4
30°	7293.6
32.5°	6721.8
35°	6091.5
37.5°	5398.3
40°	4634.3
42.5°	3938.9
45°	3315.4
47.5°	2812.1
50°	2378.4
52.5°	1768.4
55°	1088.6
57.5°	511.2
60°	331.4
62.5°	211.2
65°	121.3
67.5°	59.5
70°	29.2
72.5°	13.5
75°	11.2
77.5°	10.1
80°	7.9
82.5°	6.7
85°	4.5
87.5°	2.2
90°	0.0

(END OF REPORT)