

Scaled data based on original data using
LM-79-2024 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P1504543

Luminaire Tested: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)

Issue Date: 7/31/2026

Test Information

Test Method: LM-79-2024
Report Number: P1504543
TEST IS SCALED FROM IESNA LM-79-24 TEST DATA (G2-2602-677-47)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 7/31/2026
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: PrentaLux
Catalog Number: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)
Description: PrentaLux UHBS2 6-INCH SELECTABLE HIGH BAY 1218 LIGHT ENGINE, DOMIC WHITE
SHADE, MEDIUM DISTRIBUTION
LIGHT LEVEL 1 - 18,000 LUMENS
Light Source:
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 16454.1 lumens
Efficiency: N/A
Efficacy: 136.3 lumens/watt
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.08
Luminous Opening: Circular (Dia: 1.29' x H: 0')
CIE Type: Direct

Input Watts (W): 120.7
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P1504543

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)

Luminous Intensity Polar Plot



TEST NUMBER: P1504543

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10			
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0		
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100		
1	111	108	104	101	109	105	102	100	101	99	96	97	95	94	94	92	91	89		
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79		
3	97	89	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71		
4	91	81	74	69	89	80	73	68	77	72	67	75	70	67	73	69	66	64		
5	85	74	67	62	83	73	67	61	71	65	61	70	64	60	68	63	60	58		
6	80	69	61	56	78	68	61	56	66	60	55	65	59	55	63	58	55	53		
7	75	63	56	51	73	63	56	51	61	55	51	60	54	50	59	54	50	48		
8	70	59	52	47	69	58	51	47	57	51	46	56	50	46	55	50	46	44		
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41		
10	63	51	45	40	62	51	44	40	50	44	40	49	44	40	48	43	39	38		

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	88203
5°	88184
10°	87872
15°	87509
20°	85521
25°	82958
30°	78074
35°	63156
40°	45893
45°	29970
50°	18539
55°	14936
60°	12864
65°	13837
70°	15419
75°	16678
80°	17749
85°	18124

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°

Vertical Angle: 45°

Luminance: 29970 cd/sqm

TEST NUMBER: P1504543

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1015.7	6.2
10°-20°	2890.9	17.6
20°-30°	4192.9	25.5
30°-40°	3901.6	23.7
40°-50°	2040.4	12.4
50°-60°	950.1	5.8
60°-70°	706.8	4.3
70°-80°	548.3	3.3
80°-90°	207.4	1.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8099.6	49.2
0°-40°	12001.2	72.9
0°-60°	14991.6	91.1
0°-90°	16454.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	16454.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	10738	
5°	10694	###
15°	10290	2891
25°	9153	4193
35°	6298	3902
45°	2580	2040
55°	1043	950
65°	712	707
75°	526	548
85°	192	207
90°	0	

TEST NUMBER: P1504543

CATALOG NUMBER: PRLX-UHBS2-1218-MV-L8C5-U-A-06-WHGL-PS (3500K_L18_Medium_120V)

CANDELA DISTRIBUTION (FULL):

0°	
0°	10737.5
2.5°	10708.3
5°	10694.4
7.5°	10636.1
10°	10534.7
12.5°	10434.5
15°	10290.0
17.5°	10062.8
20°	9783.2
22.5°	9484.9
25°	9152.8
27.5°	8765.9
30°	8231.1
32.5°	7333.9
35°	6298.0
37.5°	5269.1
40°	4279.8
42.5°	3415.3
45°	2579.8
47.5°	1839.9
50°	1450.7
52.5°	1221.1
55°	1042.9
57.5°	880.9
60°	783.0
62.5°	744.6
65°	711.9
67.5°	682.8
70°	642.0
72.5°	588.4
75°	525.5
77.5°	454.4
80°	375.2
82.5°	286.6
85°	192.3
87.5°	95.5
90°	0.0

(END OF REPORT)